



USB 3.2 NANODURA Dual

The Global Leader in Specialized Storage and Memory Solutions



Key Features





- Superior Random Write performance
- Global wear leveling
- Bad block management algorithm
- High reliability
- Plug and Play with hot-swappable connection supported
- OTG Type-C connector supported Form Factor: USB flash drive (USB 3.2)
- Connector Type: Type C, supports reversible plug orientation
- Device write protect supported

The B600Sc Series NANODURA Dual universal flash drives (UFDs) are removable storage media that comply with Superspeed USB 3.2 Gen 1 specifications. With data transfer rates of up to 5 Gb/s, the B600Sc Series exceeds USB 2.0's maximum transfer speed of 480 Mb/s.

These UFDs use Type-C connectors that support reversible plug orientation and are available in 32/64/128 GB capacities to meet varied data storage requirements.

Specifications

USB 3.2 NANODURA Dual	
Product Line	Superior
	B600Sc
Interface	USB 3.2
Flash Type	TLC
Form Factor	USB Type-A USB Type-A/Type-C Dual Connector (Optional) ¹
Operating Temperature	0°C to 70°C
Power Loss Protection Options	Firmware Based
Optional SED Features	-
Capacity	32 GB to 128 GB
Performance	
USB 3.2 Sequential Read (MB/s) up to	270
USB 3.2 Sequential Write (MB/s) up to	85
USB 2.0 Sequential Read (MB/s) up to	45
USB 2.0 Sequential Write (MB/s) up to	30
Endurance and Reliability	
Endurance (TBW) ² up to	84 TB
Reliability MTBF @ 25°C	>2,000,000 hours
Reliability Number of Insertions	10,000 minimum
Others	
Dimensions (mm)	28 x 12.25 x 4.65 Dual Connector: 36.40 x 12.25 x 4.65
Certifications	CE, FCC, UKCA, RoHS
Warranty	2 years

Technologies & Add-On Services	 S.M.A.R.T.	 Firmware-based Power Loss Protection	 Advanced Wear Leveling	 SiP
Superior	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

¹ Dual connector device supports USB On-The-Go (OTG).

² Under highest Sequential write value. May vary by density, configuration and applications.

▲: Customization option available on a project basis.

Product spec and its related information are subject to change without advance notice. Please refer to www.atpinc.com for latest information

v1.0 102023

© Copyright 2023 ATP Electronics, Inc. All rights reserved.



The Global Leader in Specialized Storage and Memory Solutions

WE BUILD WITH YOU

ATP TAIWAN (HQ)

TEL: +886-2-2659-6368
sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000
sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0
sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6260-0797
sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220
sales@cn.atpinc.com



Singel 3 | B-2550 Kontich | Belgium | Tel. +32 (0)3 458 30 33 | info@alcom.be | www.alcom.be
Rivium 1e straat 52 | 2909 LE Capelle aan den IJssel | The Netherlands | Tel. +31 (0)10 288 25 00 | info@alcom.nl | www.alcom.nl