Ag57XX-LPB

SMT, Low Profile, 30W, IEEE802.3 Compliant PD Module



 World's Smallest SMT POE+ PD Module :

33mm(L)x21.5mm(W)x13mm(H)

- POE+ module compliant with IEEE 802.3af, IEEE802.3at & IEEE802.3bt
- Up to 30 Watt Output Power
- High efficiency DC/DC converter
- Industrial Temperature Range
- 1500V isolation (input to output)
- Input voltage range 37V to 57V
- Output voltage: 12V (Ag5712-LPB) or 24V (Ag5724-LPB)
- Overload, Thermal and Short-circuit protection
- Fully surface mount

Silvertel's Ag57XX is a surface mount (SMT) PoE+ module delivering up to 30 Watts of output power - requiring less than 7cm² of PCB space. This is ideal for any application where space is at a premium, such as IP Telephones, Wireless Access Points, PTZ cameras, door entry systems, monitors and remote computer terminal applications.


Ag57XX is fully compliant with IEEE802.3af, IEEE802.3at and

IEEE802.3bt standards. The device is a fixed Class 4 PD. The module works with both types of Power Sourcing Equipment (PSE) units - mid-span and end-span injectors. The high efficiency DC/DC converter operates over a wide input voltage range to provide a regulated low ripple, low noise output. The module provides built-in overload, thermal and short-circuit output protection.

Output voltage variants are available at 12V or 24V, with output adjustment up or down using a pull-up/down resistor. The module is rated over the industrial temperature range.

Ag57XX includes 1500V safety isolation as required by IEEE802.3 and to prevent earth loops.

Available as a low-profile, surface mount device, with connections via terminal blocks, allowing for close coupling and good thermal management to the host pcb. The module is designed for simple integration, requiring very few external components.



Power and Analogue Solutions

http://www.silvertel.com/

