

# EPD-4200-B1

## 42" ePaper Outdoor Open Frame Monitor



### Product Features

- Outdoor ePaper Display Kit
- Front IP65, back IP64, designed for outdoor.
- 1 USB / 1 12V DC-in as an Extended USB Display

### Specification

#### System Information

**Board** T1000 T-con board

#### Power Requirement

**DC Input** DC-12V

#### Certification

**Certification Information** CE/FCC class A

#### Panel

**LCD Size** 42"

**LCD Panel** ED420TT5

**Display Type** Eink

**Resolution** 2160 x 2880 pixels

**Backlight** option

#### I/O

**USB** 1 x USB 2.0

## Mechanical & Environmental

<b>Operating Temp.</b>	-15°C ~ 65°C
<b>Storage Temp.</b>	-20 ~ 70°C (-4 ~ 158°F)
<b>Operating Humidity</b>	40°C@95% relative humidity, non-condensing
<b>Dimension (W x L x H)</b>	676* 910 *58
<b>Weight</b>	12kg
<b>Vibration Test</b>	5Grms, IEC 60068-2-64, Random, 10 ~ 500Hz, 1hr/axis (Only for Z-axis) 0.5 Grms, IEC 60068-2-64, Random, 5~ 500Hz, 1hr/axis (Only for Z-axis)
<b>Shock Test</b>	IEC 60068-2-27, Half Sine, 11ms (Only for Z-axis)
<b>Drop Test</b>	Avalue Standard Test Criteria (ISTA-1A)
<b>IP Rating</b>	Front IP65, back IP64,

## Ordering Information

<b>Ordering Information</b>	EPD-4200-OFD-B1-1R 42"E Ink Open Frame Display EPD-4200-OFD-B1-2R 42"E Ink Open Frame Display F-light
-----------------------------	--



Singel 3 | B-2550 Kontich | Belgium | Tel. +32 (0)3 458 30 33  
info@alcom.be | www.alcom.be  
Rivium 1e straat 52 | 2909 LE Capelle aan den IJssel | The Netherlands  
Tel. +31 (0)10 288 25 00 | info@alcom.nl | www.alcom.nl