



EPM-1608

M.2 to 2-LAN Module

- > Innovative device design with 3-In-1 M.2 2280/2260/2242 fits in any host computer that has M.2 slots.
- > Suitable for M.2 slot with Key-M or Key-B based on PCI Express communication.
- > Quickly adds two independent 2.5GbE ports(with 2kv isolation) to embedded systems.

+ Spec

I/O	
Input Interface	PCI-Express. 2.0
Output Interface	2 x RJ45
Mechanical & Environmental	
Operating Temperature	Standard temperature 0°C ~ 70°C
Storage Temperature	-20°C ~ +70°C
Vibration Test	5G @5~500Hz
Shock Test	10G @ 11ms
Dimension	22mm*42mm/60mm/80mm
Form-Factor	3-In-1 M.2 2280/2260/2242 B-M Key
Software Support	
OS Information	Windows 10
Ordering Information	
Ordering Information	Standard Ordering PN: -EPM-1608D-A1R

www.avalu.com.tw



Singel 3 | B-2550 Kontich | Belgium | Tel. +32 (0)3 458 30 33

info@alcom.be | www.alcom.be

Rivium 1e straat 52 | 2909 LE Capelle aan den IJssel | The Netherlands

Tel. +31 (0)10 288 25 00 | info@alcom.nl | www.alcom.nl