

# ISS-15K5

**15.6" Rockchip RK3568 Multi-Touch Fanless Desktop self order kiosk**



## Product Features

- 15.6 inch screen, IPS LCD 1080P Resolution
- Built-in 80mm thermal printer, printing speed 250mm/s (Max)
- Built-in NFC Card reader
- Screen is covered white tempered glass, high permeability, anti-scratch
- Built-in 1D/2D scanner
- Reserved rich interface for peripherals such as cash drawer

## Specification

### System Information

Processor	Rockchip RK3568 Quad-core Cortex-A55 up to 2.0GHz
System Memory	Onboard 4GB RAM
Speaker	4Ω 3W Speaker

### Storage

Solid State Drive	Onboard 32GB eMMC
-------------------	-------------------

### Power Requirement

DC Input	+24V DC input
DC Input Connector	Mini Din 4-pin DC Jack
Power Mode	ATX

### Software Support

OS	Android 11
----	------------

## Certification

**Certification Information** CE/FCC/VCCI/BSMI

## External I/O

<b>USB Port</b>	4 x USB
<b>LAN Port</b>	1 x 10/100M by RJ-45
<b>Switch</b>	1 x Power Button 1 x Printer door Button
<b>DC in Connector</b>	+24V DC in, 4 pin
<b>Others</b>	1 x RJ11 for COM 1 x RJ12 for Cashdrawer

## Peripheral

<b>Thermal Printer</b>	Automatic paper cutting (full cut /half cut), printing paper width: 79.5±0.5mm, printing width: 72mm, paper roll specification: outer diameter--φ80mm (max), printing speed: 250mm/s (Max), printing density: 8 dots/mm, print dots: 576dots/line
<b>NFC reader</b>	Support agreement:ISO14443A Support card :Mifare (1K/4K) ; NXP S50,NXP S70, CPU card Interface: USB working frequency :13.56MHZ
<b>2D scanner</b>	1D: UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN/ISSN, Code 39, Code 39 (ASCII full code), Code 32, Trioptic Code 39, Interleaved Code 25, Industry 25 Code, Matrix 25, Codabar (NW7), 128, UCC/EAN 128 (GS1-128), ISBT128, 93, 11 (USD-8), MSI/Plessey, UK/Plessey, China Post code, GS1 DataBar (formerly: RSS) series 2D: PDF417, MicroPDF4

## Panel

<b>LCD Size</b>	15.6", 16:9
<b>LCD Control Board</b>	LCD Build-in
<b>B/L Inverter/Converter</b>	LCD Build-in
<b>Resolution</b>	1920 x 1080
<b>Touch Screen</b>	10points G+G Capacitive touch screen
<b>Touch Controller</b>	Touch Build-in

## Wireless Communication

<b>WLAN</b>	2.4G, 802.11b/g/n
<b>Bluetooth</b>	BT4.2

## Mechanical & Environmental

<b>Operating Temp.</b>	0°C ~ 40°C (32°F ~ 104°F)
<b>Storage Temp.</b>	-10°C ~ 60°C (14°F ~ 140°F)
<b>Operating Humidity</b>	40°C @ 95% Relative Humidity, Non-condensing
<b>Dimension (W x L x H)</b>	300 x 250 x 599.9mm
<b>Weight</b>	6 Kg
<b>IP Rating</b>	Front IP65
<b>Power Mode</b>	ATX
<b>System Fan</b>	Fanless
<b>Construction - Front</b>	Plastic + ABS
<b>Construction - Rear</b>	Plastic + ABS

## Component

<b>Adapter</b>	AC/DC 96W adapter 24V/4A
----------------	--------------------------