



V12/22



OFT-10WR2

10.1" Open Frame Tablet with RK3568

- > RockChip RK3568 Cortex-A55, Quad Core up to 2.0GHz
- > 2GB RAM
- > 32GB eMMC
- > PCAP Touch
- > 10/100/1000 Ethernet
- > M.2 B-Key(3042) connector socket
- > 802.11 a/b/g/n/ac Wireless LAN
- > DC 12~24V Input
- > G sensor
- > OS Image support Android 11

+ Spec

System Information

Processor	RockChip RK3568 Cortex-A55 Quad Core 2.0GHz
System Memory	2GB DDR4 RAM

Storage

Storage	32GB eMMC
----------------	-----------

Panel

LCD Size	10.1"
Resolution	800 x 1280
Luminance	350 nits
Viewing angle	160° (H/V)
Touch Type	PCAP

I/O

External I/O Connector	1 x Power Jack 1 x HDMI Port 2 x USB Type A Host 1 x RJ45 1 x Headphone Jack 1 x Reset
Internal I/O Connector	1 x USB interface , 1 x DMIC interface 1 x USB touch interface 1 x M.2 B-Key(3042) 1 x touch button control(power/vol/brightness) 1 x Power interface (12~24V) 1 x JMIPI 1 x AMIC interface 1 x Speaker interface 1 x JSEN1 interface (I2C x2) 1 x JITP1 interface 1 x Debug port 2 x RS232 interface 1 x RS232 , RS485 1 x JGPIO1 (GPIO 16bit) 1 x RTC Battery interface 1 x Micro SD slot

Wireless Communication

WLAN	802.11 a/b/g/n/ac
-------------	-------------------

Display

Multiple Display	MIP+HDMI
-------------------------	----------

Certifications

Certification Information	CE, FCC Class A
----------------------------------	-----------------

Mechanical & Environmental

Operating Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Dimension (W x L x H)	254x178x32.8 (mm)
Weight	0.7kg
Power Requirement	DC 12~24V Input
Power Mode	DC Jack, DC input 4pin header

Software Support

OS Information	Android 11
-----------------------	------------

Ordering Information

www.avalue.com.tw