

System-on-Modules (SOMs)

Laird Connectivity and Boundary Devices' embedded system-on-module (SOM) development platforms deliver highly scalable embedded processing solutions with 802.11a/b/g/n/ac and Bluetooth wireless. Built on the latest processors and wireless, and utilizing our long term software support, our SOM solutions give developers a secure, smart, connected IoT platform for deployment in the most demanding applications.




	Summit SOM 8M Plus	Nitrogen8M Plus SOM	Nitrogen8M Mini SOM	Nitrogen8M SOM	Nitrogen6 SOM V2	60 Series SOM
Processor	i.MX 8M Plus	i.MX 8M Plus	i.MX 8M Mini	i.MX 8M	i.MX 6	SAMA5D36
MPU	4x Cortex®-A53 @ 1.6 GHz	4x Cortex®-A53 @ up to 1.8 GHz	4x Cortex®-A53 @ up to 1.8 GHz	4x Cortex®-A53 @ up to 1.5 GHz	Up to 4x Cortex®-A9 @ up to 1 GHz	1x Cortex®-A5 @ 536 MHz
MCU	1x Cortex®-M7 @ 800 MHz	1x Cortex®-M7 @ 800 MHz	1x Cortex®-M4 @ 400 MHz	Cortex®-M4F @ 266 MHz	N/A	N/A
Wireless Onboard	Wi-Fi 5, BT 5.3 (NXP 88W8997)	Wi-Fi 5, BT 5	N/A	N/A	N/A	Wi-Fi 5, BT 5.1 (NXP 88W8997)
RAM	512MB, 1GB, 2GB, 4GB	2GB or 4GB LPDDR4	2GB or 4GB LPDDR4	2GB or 4GB LPDDR4	1GB or 2GB DDR3	128 MB or 256 MB LPDDR2
Storage	8GB, 16GB, or 32GB	16GB, 32GB, or 128GB	16GB, 32GB, or 128GB	16GB, 32GB, or 128GB	16GB, 32GB, or 128GB	256 MB or 512 MB NAND Flash
Multimedia	MIPI-DSI, HDMI, LVDS 1080p60 encode/decode	MIPI-DSI, HDMI, LVDS 1080p60 encode/decode	1x MIPI-DSI, 1080p60 encode/decode	MIPI-DSI, HDMI 4Kp60 decode	2x 4XGA, 1080p30 encode/ 1080p60 decode	1x 24-bit TTL RGB LCD interface
Camera	2x MIPI-CSI+ISP	2x MIPI-CSI+ISP	1x MIPI-CSI	2x MIPI-CSI	1xMIPI-CSI	12-bit Parallel
Audio	SPDIF in/out, 6x SAI, 8 channel PDM	SPDIF in/out, 6x SAI, 8 channel PDM	5x SAI, 8 channel PDM	SPDIF in/out, 6x SAI	SPDIF in/out, SAI	2x SSC
NPU	2.3 TOPS	2.3 TOPS	N/A	N/A	N/A	N/A
Form Factor	SMT	Board to Board	Edge connector	Edge connector	Edge connector	SMT
Additional Interfaces	2x USB3, 2x GbE 2x CAN/CAN FD, 1x SDIO/eMMC 12C, SPI, UART	2x USB3, 2x GbE, 2x CAN/CAN FD 1x PCIe, 1x SDIO/eMMC 12C, SPI, UART	2x USB2, 1x GbE, 1x PCIe, 2x SDIO/eMMC 12C, SPI, UART	2x USB3, 1x GbE, 2x PCIe 12C, SPI, UART	1x USB2, 1x GbE, 1x CAN, 1x SATA 12C, SPI, UART	3x USB2 2x Ethernet, 1x CAN, 1x SD/MMC 12C, SPI, UART
Size	40 x 47 mm	48 x 38 mm	69.6 x 40 mm	67.6 x 48.4 mm	57 x 63.5 mm	30 x 30 mm
Operating Temperature	-30 to +85 °C	0 to +70 °C OR -40 to +85 °C	0 to +70 °C OR -40 to +85 °C	0 to +70 °C OR -40 to +85 °C	0 to +70 °C OR -40 to +85 °C	-30 to +85 °C
Weblink	Product Page	Product Page	Product Page	Product Page	Product Page	Product Page

Single Board Computers (SBCs)



Single Board Computers from Laird Connectivity and Boundary Devices provide the host platform for your device. Providing many external interfaces, including data, audio/video, camera, wired and wireless networking, power supply connectors and more, SBCs provide the complete platform for your embedded design.



	Nitrogen 8M Mini SBC	Nitrogen 8M SBC	Nitrogen6 MAX
Chipset	NXP i.MX 8M Mini	NXP i.MX 8M Quad Core	NXP i.MX 6
MPU	4x Cortex®-A53 @ up to 1.8 GHz	4x Cortex®-A53 @ up to 1.5 GHz	Up to 4x Cortex®-A9 @ up to 1 GHz
MCU	1x Cortex®-M4 @ 400 MHz	Cortex®-M4F @ 266 MHz	N/A
Wireless Protocol	Wi-Fi 5 / Bluetooth 5.0	Wi-Fi 5 / Bluetooth 5.0	Wi-Fi 5 / Bluetooth 5.0
Interfaces	4-lane MIPI display, 4-lane MIPI camera, 1GB Ethernet, Optional PoE, PCIe, USB 2.0, Stereo audio (headphone/speaker), 12C, SPI, GPIO	4-lane MIPI display, 2x 4-lane MIPI camera, HDMI 2.0, 1GB Ethernet, 2x PCIe, 4x USB 3.0, Stereo audio (headphone/speaker), 12C, SPI, GPIO	MIPI camera, 4x display (PRGB, 2x LVDS, HDMI), 1GB Ethernet, 1x PCIe, 3x USB 2.0, Stereo audio (headphone/speaker), 12C, SPI, GPIO, 2x RS232
Size (mm)	114.3 x 88.9 mm	87 x 136.7 mm	136.7 x 87 mm
Operating Temperature	0 to +70 °C (-40 to +85 optional)	0 to +70 °C (-40 to +85 optional)	0 to +70 °C
Weblink	Product Page	Product Page	Product Page

Not quite the right fit? Consider the custom route.

Laird Connectivity and Boundary Devices have broad capabilities in design and manufacturing, and can custom-design a board to your exact specifications and price targets. Most customers are amazed at how quickly we can move a project from design to production within their target budget. On average, customers take 9-15 months to get to production; we can complete it in as little as 12 weeks. By starting with our core layout, we produce custom designs faster and more affordably.



Singel 3 | B-2550 Kontich | Belgium | Tel. +32 (0)3 458 30 33 | info@alcom.be | www.alcom.be

Rivium 1e straat 52 | 2909 LE Capelle aan den IJssel | The Netherlands | Tel. +31 (0)10 288 25 00 | info@alcom.nl | www.alcom.nl