Current Sensors All Products						
Series	type	Specification				
	()pc	Operating Principle	Primary Conductor	Ratad Current	Electrical Voltage	
F01P	F01PxxxS05L	FLUXGATE	built-in bus-bar	6~50A	+5V	
F02P	F02PxxxS05L	FLUXGATE	built-in bus-bar	6~50A	+5V	
F03P	F03PxxxS05L	FLUXGATE	built-in bus-bar	6~50A	+5V	
F23P	F23PxxxS05R	FLUXGATE	built-in bus-bar	50 <b>~</b> 100A	+5V	
	F26PxxxS05A	FLUXGATE	through-hole	50 <b>~</b> 150A	+5V	
	F26PxxxS05					



F26P	F26PxxxS12			150A	+12V
LA17	LA17PxxxS05	OPEN	built-in bus-bar	10~50A	+5V
LA37S	LA37SxxxS05 LA37SxxxS05K	OPEN	through-hole	50~600A	+5V
L01Z	L01ZxxxS05	OPEN	through-hole	50~600A	+5V
LO3S	L03SxxxD15 L03SxxxD15W	OPEN	through-hole	50~600A 50~800A	±15V
L05Z	L05Z800S15	OPEN	through-hole	800A	+15V
			1	1	1

L06P	L06PxxxS05	OPEN	through-hole	300~800A	+5V
LO7P	L07PxxxD15 L07PxxxD15S L07PxxxS05	OPEN	built-in coil	3~30A	±15V +5V
LO8P	L08PxxxD15IPV/W/IPVW	OPEN	through-hole	50~500A	±15V
L12P	L12P025D15	OPEN	built-in coil	25A	±15V
	L18PxxxD15 L18PxxxD15-OP L18PxxxD15AHV	OPEN	⊘ built-in coil∕bus-bar	3~60A	±15V
L18P	L18PxxxS05 L18PxxxS05R	e			+5V

Image: Single state in the second state in the se		L18PxxxS12				+12V
$ \begin{array}{c} 132P \times x505FS \\ 132P \times x505BFS \\ (built-in bus-bar) \end{array} \\ \begin{array}{c} 0PEN \\ 134S \times xD15 \end{array} \\ \begin{array}{c} 134S \times xD15T \\ 134S \times xD15 \end{array} \\ \begin{array}{c} 134S \times xD15 \\ 134S \times xD15 \end{array} \\ \begin{array}{c} 0PEN \\ 134S \times xD15 \end{array} \\ \begin{array}{c} 0PEN \\ 1000 \\ 10$	L31S	L31SxxxS05FS	OPEN	through-hole	50~600A	
Image: Signabular system Image: Signabul	L32P	L32PxxxS05BFS	OPEN	through-hole		
(JST Connector) L37SxxxD15M (Molex Connector) PPEN Fhrough-hole 50~600A 800A ±15V   L37SxxS05J (JST Connector) OPEN Fhrough-hole 50~600A ±5V   L37SxxS05J L37SxxS05J ±5V ±5V ±5V	L34S		OPEN	through-hole	200~1500A	±15V
L37S L37SxxxS05J (JST Connector) L37SxxxS05M L37SxxxS05M L37SxxxS05M		(JST Connector)		through-hole		±15V
		(JST Connector)			50~600A	±5V

L40S	L40SxxxD15	OPEN	through-hole	200A~1500A	±15V
L51S	L51SxxxD15L L51SxxxD15 L51SxxxD15C	OPEN	through-hole	500A~2500A	±15V
new L55S	ZL55SxxxD15	OPEN	through-hole	1500A, 2000A, 2500A	±15V
<b>S21S</b>	ZS21S180D15JN	CLOSED	through-hole	180A	±15V
S22P	S22PxxxS05P	CLOSED	built-in bus-bar	6~25A	+5V
			<u>.</u>		

S23P	S23P50/100D15 S23P50/100D15M1 S23P50/100D15M2	CLOSED	built-in bus-bar	100A	±15V
527S	⊠ <u>S27S300D15Y*</u>	CLOSED	through-hole	300A	±20V
528S	ZS28S500D24Z*	CLOSED	through-hole	500A	±24V
529S	<mark>⊠S29S1T0D24Z*</mark>	CLOSED	through-hole	1000A	±24V
530S	<u>⊠S30S2T0D24Z*</u>	CLOSED	through-hole	2000A	±24V
5425	Z <u>S42S1T0D24Z*</u>	CLOSED	through-hole	1000A	±24V
			·	·	· · · · · ·

