

Product (BXFN)	CCT Range (Nominal)	CRI (min)	Flux (Typ, 2700K)	Efficacy (lm/W)	Forward Voltage (Typ)	Forward Current (Nominal)	Dimensions (mm)
2835, 1W (21H-18C)	2700K-6500K	90	138 lm	153 lm/W	18V	50mA	3.50x2.80x0.70
2835, 1W (13H-9C)	2700K-6500K	90	125 lm	139 lm/W	9.2V	100mA	3.50x2.80x0.70
2835, 1W (13H-9D)	2700K-6500K	90	140 lm	156 lm/W	8.95 V	100mA	3.50x2.80x0.70

Product (BXFN)	CCT Range (Nominal)	CRI (min)	Flux (Typ, 2700K)	Efficacy (lm/W)	Forward Voltage (Typ)	Forward Current (Nominal)	Dimensions (mm)
2835, 0.2W (11L-37)	2700K-6500K	90	32.5 lm	170 lm/W	2.90 V	65mA	3.50x2.80x0.70
2835, 0.2W (11L-3A)	2700K-6500K	90	34 lm	182 lm/W	2.85 V	65mA	3.50x2.80x0.71
2835, 0.2W (11L-3C3)	2700K-6500K	90	35 lm	192 lm/W	2.80 V	65mA	3.50x2.80x0.72
2835, 0.2W (21L-3C4)	2700K-6500K	90	36 lm	205 lm/W	2.72 V	65mA	3.50x2.80x0.73

Product (BXEB)	Length	Width	CCT Range	CRI	SDCM	Typical Flux, 45C (4000K, 90CRI)	Typical Voltage	Drive Current	Efficacy, 45C (4000K, 90CRI)
EB Gen 3 F90-HE	140 mm	20 mm	2700K-5000K	90	3	574 lm	38.1 V	77 mA	196 lm/W
	280 mm 560 mm					1150 lm 2300 lm		154 mA 308 mA	

EB Gen 3 F90- SE -	1120 mm	20 mm	2700K-5000K	90	3	4600 lm	38.5 V	616 mA	172 lm/W
	140 mm					516 lm		77 mA	
	280 mm					1032 lm		154 mA	
	560 mm					2047 lm		308 mA	
	1120 mm					4093 lm		616 mA	