

## HCN Series NON-POLARIZED ELECTROLYTIC CAPACITOR

Non-polarized with general temperature +85°C


Load life of 1000 hours

RoHS & REACH compliant, Halogen-free

### SPECIFICATIONS

Items	Characteristics					
Operation Temperature Range	-40 ~ +85°C					
Voltage Range	6.3 ~ 50V					
Capacitance Range	0.1 ~ 100μF					
Capacitance Tolerance	±20% at 120Hz, 20°C					
Leakage Current	Leakage current ≤0.05CV or 10μA, whichever is greater (after 2 minutes application of rated voltage at 20°C) C: Nominal capacitance (μF) V: Rated voltage (V)					
Dissipation Factor (tan δ)	Measurement frequency : 120Hz, Temperature : 20°C					
	Rated Voltage (V)	6.3	10	16, 25	35, 50	
Stability at Low Temperature	Measurement frequency : 120Hz					
	Rated Voltage (V)	6.3	10	16, 25	35, 50	
Load Life	tan δ (max.)	0.24	0.20	0.17	0.15	
	Impedance Ratio	Z(-25°C) / Z(20°C)	4	3	2	2
Shelf Life	ZT/Z20 (max.)	Z(-40°C) / Z(20°C)	8	6	4	3
	After 1000 hours application of the rated voltage at 85°C (the polarity needs to exchange every 250 hours), they meet the characteristics listed below.					
Resistance to Soldering Heat	Capacitance Change	Within ±20% of initial value				
	Dissipation Factor	200% or less of initial specified value				
Marking	Leakage Current	initial specified value or less				
	After leaving capacitors under no load at 85°C for 1000 hours, they meet the specified value for load life characteristics listed above.					
After reflow soldering and restored at room temperature, they meet the characteristics listed below.						
Capacitance Change					Within ±10% of initial value	
Dissipation Factor					initial specified value or less	
Leakage Current					initial specified value or less	
Black print on the case top.						

### DRAWING (Unit: mm)



\*1. Voltage mark for 6.3V is [6V]

\*2. Applicable to Ø6.3x7.7

### DIMENSIONS (Unit: mm)

ØD x L	4 x 5.4	5 x 5.4	6.3 x 5.4	6.3 x 7.7
A	2.0	2.2	2.6	2.6
B	4.3	5.3	6.6	6.6
C	4.3	5.3	6.6	6.6
E ± 0.2	1.0	1.4	1.9	1.9
L	5.4	5.4	5.4	7.7

**DIMENSIONS & MAXIMUM PERMISSIBLE RIPPLE CURRENT**

μF	WV Code	6.3		10		16		25		35		50	
		Case size	Ripple current										
0.1	104											4 × 5.4	1.0
0.22	224											4 × 5.4	2.0
0.33	334											4 × 5.4	2.8
0.47	474											4 × 5.4	4.0
1	105											4 × 5.4	8.4
2.2	225									4 × 5.4	8.4	5 × 5.4	13
3.3	335							5 × 5.4	12	5 × 5.4	16	5 × 5.4	17
4.7	475					4 × 5.4	12	5 × 5.4	16	5 × 5.4	18	6.3 × 5.4	20
10	106			4 × 5.4	17	5 × 5.4	23	6.3 × 5.4	27	6.3 × 5.4	29	6.3 × 7.7	36
22	226	5 × 5.4	28	6.3 × 5.4	33	6.3 × 5.4	37	6.3 × 7.7	50	6.3 × 7.7	54		
33	336	6.3 × 5.4	37	6.3 × 5.4	41	6.3 × 5.4	49	6.3 × 7.7	61				
47	476	6.3 × 5.4	45	6.3 × 7.7	61	6.3 × 7.7	75						
100	107	6.3 × 7.7	82	6.3 × 7.7	85								

•Case size ØD×L(mm), ripple current (mA rms) at 85°C, 120Hz

**FREQUENCY COEFFICIENT OF ALLOWABLE RIPPLE CURRENT**

Frequency	50Hz	120Hz	300Hz	1KHz	10KHz~
Coefficient	0.70	1.00	1.17	1.36	1.50

The endurance of capacitors is reduced with internal heating produced by ripple current at the rate of halving the lifetime with every 5~10°C rise. When long life performance is required in actual use, the rms ripple current has to be reduced.

**◆ How to order**

<b>HCN</b>	<b>106</b>	<b>M</b>	<b>0035</b>	<b>0405</b>	<b>R</b>	<b>-</b>
↓	↓	↓	↓	↓	↓	↓
<u>Type</u>	<u>Capacitance code</u>	<u>Tolerance</u>	<u>Rated Voltage</u>	<u>Size Code</u>	<u>Package</u>	<u>Additional characters may be added for special requirements</u>
HCN	pF Code: 1st two digits represent significant figures 3rd digit represents multiplier (number of zeros to follow) 106 = 10uF 107 = 100uF	M: +/-20%	Code 0035: 35VDC For DC Voltage 0006: 6.3VDC 0035: 35VDC 0050: 50VDC	Code 0405: Size 4x5.4mm Size for V-chip E-cap 0405: Size 4x5.4mm 0605: Size 6.3x5.4mm 0607: Size 6.3x7.7mm	R: Tape & Reel	

Note: Specification is subject to change without further notice. For more details and updates, please visit our website.