

Hongda Capacitors is an ISO9001:2015 and IATF16949 certified factory. With more than 20 years experiences of designing and manufacturing capacitors and inductors, we have developed ourselves to be the leading global supplier in the passive components market. As the top tantalum capacitors manufacturer in China, we've obtained GJB9001C:2017 military tantalum capacitors qualification from the Ministry of Defense.

Chip Multilayer Ceramic Capacitors

HLC Chip Multilayer Ceramic Capacitors (Chip MLCC, General Purpose)				
Dielectric:	NPO	X7R	X5R	Y5V
Capacitance range:	0.1pF to 0.27μF	100pF to 47μF	100pF to 220μF	0.01μF to 100μF
Capacitance tolerance	Cap<10pF: C (±0.25pF), D (±0.5pF) Cap≥10pF: J (±5%),K (±10%)	J (±5%), K (±10%), M (±20%)	K (±10%), M (±20%)	M (±20%), Z (-20/+80%)
Rated voltage (WVDC)	4V, 6.3V, 10V, 16V, 25V, 50V, 100V, 200V, 250V, 500V, 1000V, 2000V, 3000V, 4000V			
Operating temperature	-55 to +125°C		-55 to +85°C	-25 to +85°C
Capacitance characteristic	±30ppm	±15%	±15%	+30/-80%
Case Size:	0201, 0402, 0603, 0805, 1206, 1210, 1808,1812, 1825, 2211, 2220, 2225			



Tantalum Capacitors


CA42 Radial Epoxy Dipped Tantalum Capacitor (General Purpose)	
Operating Temp.:	-55°C~+125°C; >85°C (with rated voltage derating)
DC Leakage at 25°C:	I ₀ ≤ 0.02 CRUR or 1uA (Choose the greater one)
Capacitance:	0.68μF~1000μF
Voltage Range:	6.3V, 10V, 16V, 25V, 35V, 50V
Tolerance:	K: ±10%; M: ±20% (Standard Tolerance)
Pitch Size:	2.54mm & 5.08mm
Package Type:	Bulk; Ammo Taped Package
Cross Reference:	AVX TAP; Kemet T350-T390; Nemco TB, Vishay 199D



CA45 Chip Tantalum Capacitors (General Purpose)	
Operating Temp.:	-55°C ~ +125°C; >85 °C (with rated voltage derating)
DC Leakage at 25°C:	I ₀ ≤ 0.01 CRUR or 0.5 uA (Choose the greater one)
Capacitance:	0.68μF~2200μF
Voltage Range:	2.5V, 4V, 6.3V, 10V, 16V, 20V, 25V, 35V, 50V
Tolerance:	K: ±10%; M: ±20% (Standard Tolerance)
Case Size:	A, B, C, D, E, V case (SMT)
Package Type:	Tape & Reel
SPQ/MPQ:	Reel Qty.: A B 2000pcs; C D 500pcs; E 400pcs
Cross Ref.:	AVX TAJ series F930, Kemet T491 Series, Vishay 293D




CA45L Low ESR Chip Tantalum Capacitors	
Operating Temp.:	-55°C ~ +125°C; >85 °C (with rated voltage derating)
DC Leakage at 25°C:	I ₀ ≤ 0.01 CRUR or 0.5 uA (Choose the greater one)
Capacitance:	0.68μF~1000μF
Voltage Range:	4V, 6.3V, 10V, 16V, 20V, 25V, 35V, 50V
Tolerance:	K: ±10%; M: ±20% (Standard Tolerance)
Case Size:	A, B, C, D, E, V case (SMT)
Package Type:	Tape & Reel
SPQ/MPQ:	Reel Qty.: A B 2000pcs; C D 500pcs; E 400pcs
Cross Ref.:	AVX TPS series, Kemet T494 T495, Vishay 593D



CA55 Polymer Tantalum Capacitors	
Operating Temp.:	-55°C ~ +105°C; >85 °C (with rated voltage derating)
DC Leakage at 25°C:	I ₀ ≤ 0.01CRUR
Capacitance:	0.68μF~680μF
Voltage Range:	4V, 6.3V, 10V, 16V, 20V, 25V, 35V, 50V
Tolerance:	K: ±10%; M: ±20% (Standard Tolerance)
Case Size:	A, B, C, D, E, H, V case (SMT)
Package Type:	Tape & Reel
Cross Ref.:	AVX TCJ series, Kemet T520 Series, Vishay T55



QCA45 Chip Tantalum Capacitors (Automotive Grade)	
Operating Temp.:	-55°C ~ +125°C; >85 °C (with rated voltage derating)
DC Leakage at 25°C:	I ₀ ≤ 0.01CRUR or 0.5 uA (Choose the greater one)
Capacitance:	0.68μF~680μF
Voltage Range:	4V, 6.3V, 10V, 16V, 20V, 25V, 35V, 50V
Tolerance:	K: ±10%; M: ±20% (Standard Tolerance)
Case Size:	A, B, C, D, E, H, V case (SMT)
Package Type:	Tape & Reel
SPQ/MPQ:	Reel Qty.: A B 2000pcs; C D 500pcs; E 400pcs
Cross Ref.:	AVX TAJ series, Kemet T489/T490/T491 series



SMD Electrolytic Capacitors

HCS Series 85°C 2000 Hours V-Chip Aluminum Electrolytic Capacitor (SMD E-CAP) HVS Series: Standard, 85°C V-chip aluminum electrolytic capacitors Temperature: -40°C~ +85°C Load life: 2000 hrs Voltage: 4~450V DC Capacitance: 0.1~ 10000μF Tolerance: ±20% at 120Hz, 20°C Size: 4x5.4, 5x5.4, 6.3x5.4, 6.3x7.7, 8x10.5, 10x10.5, 10x13.5,12.5x13.5, 12.5x16, 16x16.5, 18x16.5, 18x18.5		HCH Series: High Voltag, 105°C V-chip aluminum electrolytic capacitors Temperature: -40°C ~ +105°C Load life: 3000 hrs Voltage: 160~450V DC Capacitance: 3.3~ 100μF Tolerance: ±20% at 120Hz, 20°C Size: 10x13.5, 12.5x13.5, 12.5x16, 16x16.5	
HCK Series 105°C 2000 Hours V-Chip Aluminum Electrolytic Capacitor (SMD E- CAP) HCK Series: Standard, 105°C V-chip aluminum electrolytic capacitors Temperature: -40°C~ +85°C Load life: 2000 hrs Voltage: 4~450V DC Capacitance: 0.1~ 8200μF Tolerance: ±20% at 120Hz, 20°C Size: 4x5.4, 5x5.4, 6.3x5.4, 6.3x7.7, 8x10.5, 10x10.5, 10x13.5,12.5x13.5, 12.5x16, 16x16.5, 18x16.5, 18x18.5		HHU Series: High Voltage, 105°C V-chip aluminum electrolytic capacitors Temperature: -40°C ~ +105°C Load life: 5000 hrs Voltage: 160~450V DC Capacitance: 3.3~ 47μF Tolerance: ±20% at 120Hz, 20°C Size: 8x12.5, 10x10.5, 10x13.5,12.5x13.5 ,12.5x16	
HLZ -55~+105°C 2000 hrs. Load Life Low Impedance SMD E-Cap HLZ Series: Low Impedance, 105°C V-chip aluminum electrolytic capacitors Temperature: -55°C~ +105°C Load life: 1000-2000 hrs Voltage: 6.3~50V DC Capacitance: 0.1~ 4700μF Tolerance: ±20% at 120Hz, 20°C Size: 4x5.4, 5x5.4, 6.3x5.4, 6.3x7.7, 8x10.5, 10x10.5, 10x13.5,12.5x13.5 12.5x16 16x16.5		HKH -40~+ 125°C 5000 hrs. Load Life High Temperature SMD E-Cap HKH Series: High Temperature, 125°C V-chip aluminum electrolytic capacitors Temperature: -40°C ~ +125°C Load life: 1000-5000 hrs Voltage: 10~450V DC Capacitance: 3.3~ 4700μF Tolerance: ±20% at 120Hz, 20°C Size: 4x5.8, 5x5.8, 6.3x5.8, 6.3x7.7, 8x10.5, 10x10.5, 10x13.5,12.5x13.5 12.5x16 16x16.5	
HKZ -55~+ 105°C Extremely Low Impedance SMD E- Cap HKZ Series: Low Impedance, 105°C V-chip aluminum electrolytic capacitors Temperature: -55°C~ +105°C Load life: 1000-3000 hrs Voltage: 6.3~50V DC Capacitance: 4.7~ 4700μF Tolerance: ±20% at 120Hz, 20°C Size: 4x5.8, 5x5.8, 6.3x5.8, 6.3x7.7, 8x10.5, 10x10.5, 10x13.5,12.5x13.5 12.5x16 16x16.5		HEL -55~+ 105°C 3000 hrs. Load Life Long life Assurance SMD E-Cap HEL Series: Long life, 105°C V-chip aluminum electrolytic capacitors Temperature: -55°C ~ +105°C Load life: 2000-3000 hrs Voltage: 6.3~50V DC Capacitance: 0.1~ 1500μF Tolerance: ±20% at 120Hz, 20°C Size: 4x5.8, 5x5.8, 6.3x5.8, 6.3x7.7, 8x10.5, 10x10.5, 10x13.5,12.5x13.5, 12.5x16, 16x16.5	
HFZ -55~+105°C Long life, Extremely Low Impedance SMD E-Cap HFZ Series: Low Impedance, 105°C V-chip aluminum electrolytic capacitors Temperature: -55°C~ +105°C Load life: 2000-5000 hrs Voltage: 6.3~100V DC Capacitance: 3.3~ 8200μF Tolerance: ±20% at 120Hz, 20°C Size: 4x5.8, 5x5.8, 6.3x5.8, 6.3x7.7, 8x10.5, 10x10.5, 10x13.5,12.5x13.5, 12.5x16, 16x16.5, 18x16.5,18x18.5		HKL 55~+ 105°C 5000 hrs. Load Life Long life Assurance SMD E-Cap HKL Series: Long life, 105°C V-chip aluminum electrolytic capacitors Temperature: -55°C ~ +105°C Load life: 3000-5000 hrs Voltage: 6.3~100V DC Capacitance: 0.1~ 1500μF Tolerance: ±20% at 120Hz, 20°C Size: 4x5.8, 5x5.8, 6.3x5.8, 6.3x7.7, 8x10.5, 10x10.5, 10x13.5,12.5x13.5, 12.5x16, 16x16.5	
HCP -40~ +85°C 3000 hrs. Load Life High Voltage, Long life SMD E: Cap HCP Series: High Voltage, 85°C V-chip aluminum electrolytic capacitors Temperature: -40°C~ +85°C Load life: 3000 hrs Voltage: 160~450V DC Capacitance: 3.3~ 100μF Tolerance: ±20% at 120Hz, 20°C Size: 10x13.5,12.5x13.5,12.5x16,16x16.5		HSC -40~+85°C 2000 hrs. Load Life Low Leakage Current SMD E: Cap HSC Series: Low Leakage Current, 85°C V-chip aluminum electrolytic capacitors Temperature: -40°C ~ +85°C Load life: 2000 hrs Voltage: 6.3~50V DC Capacitance: 0.1~ 220μF Tolerance: ±20% at 120Hz, 20°C Size: 4x5.4, 5x5.4, 6.3x5.4, 6.3x7.7	
HCN -40~+85°C 1000 hrs. Load Life Non-polarized HCN Series: Load Life Non-polarized Temperature: -40°C~ +85°C Load life: 1000 hrs Voltage: 6.3~50V DC Capacitance: 0.1~ 100μF Tolerance: ±20% at 120Hz, 20°C Size: 4x5.4, 5x5.4, 6.3x5.4, 6.3x7.7		HKP -55~+ 105°C 1000 hrs. Load Life Non-polarized HKP Series: Load Life Non-polarized Temperature: -55°C ~ +105°C Load life: 1000 hrs Voltage: 6.3~50V DC Capacitance: 0.1~ 47μF Tolerance: ±20% at 120Hz, 20°C Size: 4x5.4, 5x5.4, 6.3x5.4	

SMD Electrolytic Capacitors





HVS -40°C ~+85°C 2000 hrs V-Chip SMD Aluminum Electrolytic Capacitor		HVH -40°C ~+105°C 2000 hrs High Voltage SMD Aluminum Electrolytic Capacitor	
HVS Series: Standard Temperature: -40°C~+85°C Load life: 2000 hrs Voltage: 4V~400V DC Capacitance: 0.1 ~ 10000µF Tolerance: ±20% at 120Hz, 20°C Size: 4x5.4, 5x5.4, 6.3x5.4, 6.3x7.7, 6.3x10.5, 8x10.5, 10x10.5, 10x12.5, 10x13.5, 12.5x13.5, 12.5x16, 16x16.5, 18x16.5, 18x21.5		HVH Series: High Voltage, High Capacitance Temperature: -40°C ~ +105°C Load life: 2000 hrs Voltage: 4 ~ 400V DC Capacitance: 0.1 ~ 8200µF Tolerance: ±20% at 120Hz, 20°C Size: 4x5.4, 5x5.4, 6.3x5.4, 6.3x7.7, 6.3x10.5, 8x10.5, 10x10.5, 10x12.5, 10x13.5, 12.5x13.5, 12.5x16, 16x16.5, 18x16.5, 18x21.5	
HVD -55°C~+105°C 2000-5000 hrs Low Impedance Long Life SMD E-Cap		HJVD -55°C~+105°C 2000-10000 hrs Extra Lower Impedance High Voltage SMD E-Cap	
HVD Series: Low Impedance, Long Life, High Capacitance Temperature: -55°C~+105°C Load life: 2000-5000 hrs Voltage: 6.3V~50V DC Capacitance: 1 ~ 8200µF Tolerance: ±20% at 120Hz, 20°C Size: 4x5.4, 5x5.4, 6.3x5.4, 6.3x7.7, 6.3x10.5, 8x10.5, 10x10.5, 10x12.5, 10x13.5, 12.5x13.5, 12.5x16, 16x16.5, 18x16.5, 18x21.5		HJVD Series: Long Life, Extra Lower Impedance, High Voltage Temperature: -55°C ~ +105°C Load life: 2000-10000 hrs Voltage: 63 ~ 450V DC Capacitance: 1 ~ 680µF Tolerance: ±20% at 120Hz, 20°C Size: 4x5.4, 5x5.4, 6.3x5.4, 6.3x7.7, 6.3x10.5, 8x10.5, 10x10.5, 10x12.5, 10x13.5, 12.5x13.5, 12.5x16, 16x16.5, 18x16.5, 18x21.5	

Polymer Aluminum Electrolytic Capacitors

HMB SMD High Capacitance Ultra-Low ESR Conductive Polymer E-cap		HE2 Radial Low ESR Conductive Polymer E-Cap	
HMB Series: Ultra-Low ESR Temperature: -55°C~+105°C Load life: 2000 hrs Voltage: 2.5V~25V DC Capacitance: 100 ~ 1000µF Tolerance: ±20% at 120Hz, 20°C Size: Φ5, 6.3, 8, 10mm are available		HE2 Series: Low ESR, High Capacitance Temperature: -55°C~+105°C Load life: 2000 hrs Voltage: 2.5V~25V DC Capacitance: 68 ~ 1500µF Tolerance: ±20% at 120Hz, 20°C Size: Φ5, 6.3, 8, 10mm are available	
HE2 Radial High Voltage Conductive Polymer E-Cap		HH2 Radial High Voltage Conductive Polymer E-Cap	
HE2 Series: High Voltage Temperature: -55°C~+105°C Load life: 2000 hrs Voltage: 35V~100V DC Capacitance: 10 ~ 470µF Tolerance: ±20% at 120Hz, 20°C Size: Φ5, 6.3, 8, 10mm are available		HH2 Series: High Voltage Temperature: -55°C~+105°C Load life: 2000 hrs Voltage: 35V~100V DC Capacitance: 10 ~ 470µF Tolerance: ±20% at 120Hz, 20°C Size: Φ5, 6.3, 8, 10mm are available	

Polymer capacitor is a upgrade level capacitor with better performance: ROHS & REACH compliant, Halogen-free
Featured with ultra-low ESR and high ripple current
Excellent performance at high or low temperature, and even keep great characteristics at -55°C. Widely used for IT products, PD power supply, LED devices, 5G industry, and so on.



Multilayer Chip Beads

HDGB Series of Multilayer Chip Ferrite Bead		HDHB Series of Multilayer Chip High Frequency Bead	
Impedance: 1~3500 Ω Tolerance: ±25% DCR: 0.01~3 Ω Rated Current: 0.1~3 A Profile Feature: Lead-Free Size: 1005[0402], 1608[0603], 2012[0805], 3216[1206]		Impedance: 1~3500 Ω Tolerance: ±25% DCR: 0.01~3 Ω Rated Current: 0.05~3 A Profile Feature: Lead-Free Size: 0603[0201], 1005[0402], 1608[0603], 2012[0805]	
HDLB Series of Multilayer Chip Large Current Bead		HDSB Series Multilayer Chip Sharp Bead	
Impedance: 1~3500 Ω Tolerance: ±25% DCR: 0.01~2 Ω Rated Current: 0.1~10 A Profile Feature: Lead-Free Size: 1005[0402], 1608[0603], 2012[0805], 3216[1206]		Impedance: 1~3500 Ω Tolerance: ±25% DCR: 0.01~2 Ω Rated Current: 0.1~3 A Profile Feature: Lead-Free Size: 1005[0402], 1608[0603], 2012[0805], 3216[1206]	

Chip Inductors

HDCI Series Multilayer Chip Ceramic Inductor		HDFI Series Multilayer Chip Ferrite Inductor	
Inductance: 0.6~470uH Tolerance: S: ±0.3%; D: ±0.5%; J: ±5%; K: ±10% DCR: 0.05~6.0 Ω Rated Current: 0.05~1 A Profile Feature: Lead-Free Size: 0603[0201], 1005[0402], 1608[0603], 2012[0805]		Inductance: 0.047~100uH Tolerance: J: ±5%; K: ±10%; M: ±20%; N: ±30% DCR: 0.2~3.45 Ω Rated Current: 0.001~0.3 A Profile Feature: Lead-Free Size: 1005[0402], 1608[0603], 2012[0805], 3216[1206]	

Chip Inductors

HDTC Series Chip Inductor Precision Winding [High Q] Ceramic Type		HTF Series Chip Inductor Precision Winding [High Q] Ferrite Type	
Inductance: 1~1000uH Tolerance: B: ±0.1nH; C: ±0.2nH; S: ±0.3nH; D: ±0.5nH; G: ±2%; H: ±3%; J: ±5%; K: ±10% DCR: 0.012~4.35 Ω Rated Current: 0.03~3.5 A Profile Feature: Lead-Free Size: 1005[0402], 1608[0603], 2012[0805], 3216[1206], 3225[1210]		Inductance: 0.02~680uH Tolerance: J: ±5%; K: ±10% DCR: 0.028~90 Ω Rated Current: 0.01~2.5 A Profile Feature: Lead-Free Size: 1005[0402], 1608[0603], 2012[0805], 3216[1206], 3225[1210]	

Power Inductors

HDFL Series of Multilayer Chip Ferrite Large Current Inductor		SMD power inductors have the characteristics of high permeability, high current, low impedance, low loss, small size, etc.	
Inductance: 1~22uH Tolerance: K: ±10%; M: ±20%; N: ±30% DCR: 0.1~1.0 Ω Irms: 0.1~2.0 A Profile Feature: Lead-Free Size: 1608[0603], 2012[0805], 2016[0806], 2520[1008]		Main applications: Automotive power conversion, DC/DC converters, Switch-mode power supplies, High-current PoL, Power supplies, Digital product, Network communication, etc.	
HPIM Series Power Inductor Small Size Molding Type		HAPM Series Power Inductor Big Size Molding Type	
Inductance: 0.11~2.2uH Tolerance: K: ±10%; M: ±20%; N: ±30% DCR: 0.01~200 Ω Isat: 2.0~10 A Irms: 1.8~6.0 A Profile Feature: Lead-Free Size: 201208, 201210, 201610, 202510		Inductance: 0.47~22uH Tolerance: K: ±10%; M: ±20%; N: ±30% DCR: 1.3~200 Ω Isat: 2.0~10 A Irms: 1~40 A Profile Feature: Lead-Free Size: 0420, 0530, 0630, 1040, 1335, 1350, 1365	
HPIH Series Power Inductor Wire Wound[NR] Ferrite Type		HPIE Series Power Inductor Wire Wound[NR] Ferrite Type	
Inductance: 0.2~5uH Tolerance: K: ±10%; M: ±20%; N: ±30% DCR: 0.02~2.5 Ω Isat: 0.3~6 A Irms: 0.2~5 A Profile Feature: Lead-Free Size: 201610, 252010, 252012		Inductance: 0.2~30uH Tolerance: K: ±10%; M: ±20%; N: ±30% DCR: 0.02~2 Ω Isat: 0.3~5 A Irms: 0.2~5 A Profile Feature: Lead-Free Size: 201608, 201610, 252008, 202010	
HPIA / HPIAL Series Power Inductor Wire Wound[NR] Alloy Type		HPIT Series Power Inductor Wire Wound[NR] Ferrite Type	
Inductance: 0.2~10uH Tolerance: K: ±10%; M: ±20%; N: ±30% DCR: 0.01~2 Ω Isat: 0.1~10 A Irms: 0.1~50 A Profile Feature: Lead-Free Size: 201608, 201610, 252008, 252010, 252012, 3012, 3015		Inductance: 0.4~6800uH Tolerance: K: ±10%; M: ±20%; N: ±30% DCR: 0.007~30 Ω Isat: 0.2~20 A Irms: 0.1~10 A Profile Feature: Lead-Free Size: 252010, 252012, 3010, 3012, 3015, 4012, 4018, 4020, 4030, 5020, 5040, 6028, 6045, 8040, 8065	
HDCDH Series Power Inductor Coil Type [Whole Shield]		HDCDRH Series Power Inductor Coil Type [Whole Shield]	
Inductance: 3~100uH Tolerance: K: ±10%; M: ±20%; N: ±30% DCR: 0.015~0.5 Ω Isat: 0.5~6 A Irms: 0.5~7 A Profile Feature: Lead-Free Size: 8D28, 8D38, 8D43		Inductance: 1~350uH Tolerance: K: ±10%; M: ±20%; N: ±30% DCR: 0.005~2 Ω Isat: 0.5~10 A Irms: 0.5~7 A Profile Feature: Lead-Free Size: 104, 105	
HDSFD Series Power Inductor Coil Type [Whole Shield]		HSDSRH Series Power Inductor Coil Type [Whole Shield]	
Inductance: 1~100uH Tolerance: K: ±10%; M: ±20%; N: ±30% DCR: 0.01~2 Ω Rated Current: 0.2~4 A Profile Feature: Lead-Free Size: 2D11, 2D11HP, 4D18, 4D28, 5D18, 5D28, 6D28		Inductance: 1~1000uH Tolerance: K: ±10%; M: ±20%; N: ±30% DCR: 0.005~10 Ω Rated Current: 0.1~10 A Profile Feature: Lead-Free Size: 73, 74, 124, 125, 127	
HDSL Series Power Inductor Coil Type [Whole Shield]		HSDS Series Power Inductor Coil Type [No Shield]	
Inductance: 1~1000uH Tolerance: K: ±10%; M: ±20%; N: ±30% DCR: 0.01~4 Ω Rated Current: 0.1~5 A Profile Feature: Lead-Free Size: 0628, 0645, 0745, 0755, 10145, 12555		Inductance: 1~500uH Tolerance: K: ±10%; M: ±20%; N: ±30% DCR: 0.03~2 Ω Rated Current: 0.2~4 A Profile Feature: Lead-Free Size: HSDS32, HSDS43, HSDS54, HSDS75	

Common Mode Choke Coil

HDRC Series Winding Wire Common Mode Choke Coil	
Impedance: 1~3500 Ω	 <p>Hongda HDRC Series Winding Wire Common Mode Choke Coil Features:</p> <ol style="list-style-type: none"> 1. Wire-wound patch structure, small size 2. Good suppression effect on high frequency common mode noise 3. Good solderability and resistance to soldering 4. Lead-free and RoHS REACH compliant <p>APPLICATIONS</p> <p>USB interface of PC and peripherals, LVDS line of LCD</p>
Tolerance: ±25%	
DCR: 0.01~3 Ω	
Rated Current: 0.1~3 A	
Profile Feature: Lead-Free	
Size: 2012M, 1210M, 3216M, 3225M, 4520M, 4532M, 7060M	

Radial Aluminum Electrolytic Capacitors

RGR Standard Series Radial Aluminum Electrolytic Capacitors		RRL Standard Series Radial Aluminum Electrolytic Capacitors	
Series: Standard Series		Series: Standard Series	
Temperature: -40~+85 °C		Temperature: -25~+105 °C	
Voltage Range: 6.3 ~ 450 V		Voltage Range: 6.3 ~ 450 V	
Capacitance: 0.1~33000 uF		Capacitance: 0.1~22000 uF	
Load Life: 2000 hours		Load Life: 2000 hours	
RRA Standard Series Radial Aluminum Electrolytic Capacitors		RRN Standard Series Radial Aluminum Electrolytic Capacitors	
Series: Standard Series		Series: Standard Series	
Temperature: -25~+105 °C		Temperature: -25~+105 °C	
Voltage Range: 400 ~ 500 V		Voltage Range: 200 ~ 450V	
Capacitance: 2.2-47 uF		Capacitance: 22-270 uF	
Load Life: 2000 hours		Load Life: 2000 hours	
RGF Series Low Impedance High Ripple Current Radial E-Cap		RGE Series Low Impedance High Ripple Current Long Life Radial E-Cap	
Series: Low Impedance, High Ripple Current		Series: Low Impedance, High Ripple Current, Long Life	
Temperature: -40~+105 °C		Temperature: -40~+105 °C	
Voltage Range: 6.3 ~ 100 V		Voltage Range: 6.3 ~ 100 V	
Capacitance: 3.3~4700 uF		Capacitance: 15~3900 uF	
Load Life: 1000 ~ 4000 hours		Load Life: 3000 ~ 6000 hours	
RRC Series Low Impedance High Ripple Current Long Life Radial E-Cap		RRL Series High Temperature High Ripple Current High Voltage Long Life Radial E-Cap	
Series: Low Impedance, High Ripple Current, Long Life		Series: High Temperature, High Ripple Current, High Voltage, Long Life	
Temperature: -40~+105 °C		Temperature: -25~+130 °C	
Voltage Range: 6.3 ~ 50V		Voltage Range: 160 ~ 450 V	
Capacitance: 15~3900 uF		Capacitance: 1.5 ~ 100 uF	
Load Life: 4000 ~ 10000 hours		Load Life: 5000 ~ 6000 hours	
RLW Series High Temperature Radial E-Cap		RLX Series High Temperature High Voltage Radial E-Cap	
Series: High Temperature		Series: High Temperature, High Voltage	
Temperature: -40~+125 °C		Temperature: -40~+130 °C	
Voltage Range: 10 ~ 50 V		Voltage Range: 160 ~ 450 V	
Capacitance: 3.3~3900 uF		Capacitance: 1.5~220 uF	
Load Life: 1000~200 hours		Load Life: 3000 ~ 4000 hours	
RMZ Series High Voltage Long Life Radial E-Cap		RFZ Series High Voltage Long Life Radial E-Cap	
Series: High Voltage, Long Life		Series: High Voltage, Long Life	
Temperature: -40~+105 °C		Temperature: -40~+105 °C	
Voltage Range: 160 ~ 450 V		Voltage Range: 160 ~ 500 V	
Capacitance: 1.5 ~ 100 uF		Capacitance: 10~331 uF	
Load Life: 5000 ~ 6000 hours		Load Life: 8000 ~ 10000 hours	
RLZ Series High Voltage Long Life Radial E-Cap		RRZ Series High Voltage High Reliability Radial E-Cap	
Series: High Voltage, Long Life		Series: High Voltage, High Reliability	
Temperature: -40~+105 °C		Temperature: -40~+105 °C	
Voltage Range: 160 ~ 500 V		Voltage Range: 160 ~ 450 V	
Capacitance: 1~220 uF		Capacitance: 1~220 uF	
Load Life: 10000 ~ 12000 hours		Load Life: 3000 hours	
RGK Series Super Low Temperature High Voltage Radial E-Cap		RFM Series Low Leakage Radial E-Cap	
Series: Super Low Temperature, High Voltage		Series: Low Leakage	
Temperature: -55~+105 °C		Temperature: -40~+105 °C	
Voltage Range: 160 ~ 500 V		Voltage Range: 6.3 ~ 100 V	
Capacitance: 1~220 uF		Capacitance: 0.1~3300 uF	
Load Life: 2000~5000 hours		Load Life: 2000 hours	

Radial Aluminum Electrolytic Capacitors

RKS Low Profile Series Radial Aluminum Electrolytic Capacitors		RLM Low Profile Series Radial Aluminum Electrolytic Capacitors	
Series: Low Profile Series		Series: Low Profile Series	
Temperature: -40~+105 °C		Temperature: -40~+85 °C	
Voltage Range: 6.3 ~ 50 V		Voltage Range: 4 ~ 50 V	
Capacitance: 0.1~220 uF		Capacitance: 0.1~470 uF	
Load Life: 1000 hours		Load Life: 2000 hours	
RKF Low Profile Series Radial Aluminum Electrolytic Capacitors		RSC Low Profile Series Radial Aluminum Electrolytic Capacitors	
Series: Low Profile Series		Series: Low Profile Series	
Temperature: -40~+105 °C		Temperature: -40~+85 °C	
Voltage Range: 4 ~ 50 V		Voltage Range: 6.3 ~ 63 V	
Capacitance: 0.1~100 uF		Capacitance: 0.1~470 uF	
Load Life: 1000 hours		Load Life: 2000 hours	
RLK Miniature Series Radial Aluminum Electrolytic Capacitors		RNB Bi-Polar Series Radial Aluminum Electrolytic Capacitors	
Series: Miniature Series		Series: Bi-Polar	
Temperature: -40~+105 °C		Temperature: -40~+85 °C	
Voltage Range: 400 ~ 450 V		Voltage Range: 6.3 ~ 100 V	
Capacitance: 4.7~100 uF		Capacitance: 0.47~6800 uF	
Load Life: 2000 hours		Load Life: 2000 hours	
RFB Bi-Polar Series Radial Aluminum Electrolytic Capacitors		RNE Bi-Polar Series Radial Aluminum Electrolytic Capacitors	
Series: Bi-Polar		Series: Bi-Polar	
Temperature: -45~+105 °C		Temperature: -40~+85 °C	
Voltage Range: 6.3 ~ 100 V		Voltage Range: 50 ~ 100 V	
Capacitance: 0.47~1000 uF		Capacitance: 1~68 uF	
Load Life: 2000 hours		Load Life: 2000 hours	
RLP Series Snap-in Terminal Radial Aluminum Electrolytic Capacitors		RHP Series Snap-in Terminal Radial Aluminum Electrolytic Capacitors	
Series: Snap-in		Series: Snap-in	
Temperature: -40~+85 °C		Temperature: -40~+105 °C	
Voltage Range: 10 ~ 450 V		Voltage Range: 10 ~ 450 V	
Capacitance: 56~82000 uF		Capacitance: 47~56000 uF	
Load Life: 2000 hours		Load Life: 2000 hours	
RGP Series Snap-in Terminal Radial Aluminum Electrolytic Capacitors		RIP Series Snap-in Terminal Radial Aluminum Electrolytic Capacitors	
Series: Snap-in		Series: Snap-in, Long Life	
Temperature: -40~+105 °C		Temperature: -40~+105 °C	
Voltage Range: 10 ~ 450 V		Voltage Range: 10 ~ 400 V	
Capacitance: 56~47000 uF		Capacitance: 56~47000 uF	
Load Life: 2000 hours		Load Life: 5000 hours	
RCP Series Snap-in Terminal Radial Aluminum Electrolytic Capacitors		RPN Series Snap-in Terminal Radial Aluminum Electrolytic Capacitors	
Series: Snap-in, Super Low Temperature		Series: Snap-in, High Capacitance	
Temperature: -55~+105 °C		Temperature: -40~+85 °C	
Voltage Range: 160 ~ 450 V		Voltage Range: 10 ~ 450 V	
Capacitance: 56~47000 uF		Capacitance: 270~680000 uF	
Load Life: 2000 hours		Load Life: 2000 hours	
RMN Series Snap-in Terminal Radial Aluminum Electrolytic Capacitors		<p>Aluminum electrolytic radial capacitors are used in various types of electronic equipment. It is a low-cost component that is critical to the reliable performance of your electronic devices.</p> <p>Hongda Capacitors is your reliable supplier:</p> <p>RoHS REACH Compliant, Cost Efficiency, Fast delivery 4 weeks, Stable supply</p>	
Series: Snap-in, High Capacitance			
Temperature: -40~+105 °C			
Voltage Range: 160 ~ 500 V			
Capacitance: 180~680000 uF			
Load Life: 2000 hours			

Thick Film Chip Resistors

Thick Film Chip Resistors	
<p>Size: 01005[0402], 0201[0603], 0402[1005], 0603[1608], 0805[2012], 1206[3216], 1210[3225], 1812[4532], 2010[5025], 2512[6332]</p>	 <p>Small size & light weight.</p> <p>RoHS, REACH, Halogen free compliances.</p> <p>Reduction of assembly costs and matching with placement machine.</p> <p>Suitable for both wave & re-flow soldering.</p> <p>Applications: Navigator (GPS), Mobile Phone, Telecom, PDA, Set box, Meter, etc</p>