

MPE-150C

150W, High Isolation AC/DC Power Supplies



Key Features:

- 150W Output Power
- 85-264 VAC Input
- 4,000 VAC Isolation
- Efficiency to 89%
- -30°C to +70°C Temp
- Meets EN 55032 B
- >300 kHour MBTF
- OVC Class III
- UL62368 Approval

Electrical Specifications

Specifications typical @ +25°C, nominal input voltage & rated output current, unless otherwise noted. Specifications subject to change without notice.

Input

Parameter	Conditions	Min.	Typ.	Max.	Units
Input Voltage Range	AC Input	85		264	VAC
	DC Input	120		370	VDC
Input Frequency		47		63	Hz
Input Current	115 VAC			3.0	A
	230 VAC			1.5	A
Inrush Current (Cold Start)	115 VAC		30		A
	230 VAC		60		A
Leakage Current	240 VAC			0.75	mA

Output

Parameter	Conditions	Min.	Typ.	Max.	Units
Output Voltage Accuracy	Full Load	Normal Temperature		±1	%
		Low/High Temperature		±3	
Line Regulation	Rated Load		±0.5		%
Load Regulation	0-100% Load		±0.5		%
Ripple & Noise (20 MHz)	12, 15V Output			150	mV P - P
	24, 36, 48V Outputs			200	
Hold-Up Time	115 VAC	8			ms
	230 VAC	16			
Standby Power Consumption				0.5	W
Power Derating	85 - 100 VAC	-30°C to -25°C	5		% / °C
	12V	+45°C to +70°C	2		
	15, 24, 36, 48V	+50°C to +70°C	2.5		
	Input Voltage Derating	85 - 100 VAC	1.33		
Temperature Coefficient	0 to 50°C, 230 VAC		±0.03		% / °C
Short Circuit Protection	Recovery time <5s after short circuit removed	Hiccup, Continuous, Self-Recovery			
Over Current Protection	For more than 5 seconds, turn off output, restart	110			%Io

General

Parameter	Conditions	Min.	Typ.	Max.	Units
Isolation Voltage	Input - Ground	2,000			VAC
	Input - Output	4,000			
	Output - Ground	1,250			
Isolation Resistance	See Note 6	100			MΩ
Switching Frequency			65		kHz

EMI Characteristics

Parameter	Standard	Criteria	Level
Radiated Emissions, See Page 4	CISPR32/EN 55032		Class B
Conducted Emissions	CISPR32/EN 55032		Class B

Environmental

Parameter	Conditions	Min.	Typ.	Max.	Units
Operating Temperature Range	Ambient	-30		+70	°C
Storage Temperature Range		-40		+85	°C
Cooling	Free Air Convection				
Operating Humidity	Non-condensing	20		90	%RH
Storage Humidity		10		95	

Physical

Case Size	6.26 x 3.82 x 1.18 in (See Mechanical Drawing on Page 4)
Case Material	Metal (AL1100, SGCC)
Weight	14.46 oz (410g) (See Mechanical Drawing on Page 4)

Reliability Specifications

Parameter	Conditions	Min.	Typ.	Max.	Units
MTBF	MIL HDBK 217F, 25°C, Gnd Benign	0.3			MHours
Safety Standards	UL/cUL 62368-1 Recognition (UL Certificate)				
Safety Class	Class I				



RoHS

MicroPower Direct

46 Eastman Street
Unit 1
Easton, MA 02375
USA

T: (781) 344-8226
F: (781) 344-8481

E: sales@micropowerdirect.com
W: www.micropowerdirect.com



www.micropowerdirect.com

Singel 3 | B-2550 Kontich | Belgium | Tel. +32 (0)3 458 30 33 | info@alcom.be | www.alcom.be

Rivium 1e straat 52 | 2909 LE Capelle aan den IJssel | The Netherlands | Tel. +31 (0)10 288 25 00 | info@alcom.nl | www.alcom.nl

Model Selection Guide

UL	Model Number	Input		Output				Over Voltage Protection (Max) (VDC)	Output Capacitive Load (μ F Max)	Efficiency (% Typ)
		Current (mA)		Voltage (VDC)	Voltage Adjustable Range (VDC)	Current (A, Max)	Power (W)			
		115 VAC	230 VAC							
•	MPE-150C-12	4000	2000	12	10.2 - 13.8	12.5	150	18	10000	86
	MPE-150C-15	4000	2000	15	13.5 - 18	10	150	21.75	6000	87
•	MPE-150C-24	4000	2000	24	21.6 - 28.8	6.5	156	33.6	2400	88
	MPE-150C-36	4000	2000	36	32.4 - 39.6	4.3	154.8	48.6	1200	88
	MPE-150C-48	4000	2000	48	43.2 - 52.8	3.3	158.4	60	600	89

* MPE-150C-12, -24 have UL/cUL 62368-1 recognition (UL certificate). Contact factory for safety standard status of other models.


Notes:

1. The "tip and barrel method" is used for ripple and noise test, output parallel 47 μ F electrolytic capacitor and 0.1 μ F ceramic capacitor.
2. Output short circuit protection is provided by a "hiccup mode" circuit. The unit recovers automatically when the fault condition is removed.
3. Input-output isolation is tested for 60 seconds.
4. A temperature derating of 5 $^{\circ}$ C/1000m is required for operating altitude greater than 2000m.


5. The output voltage can be adjusted by the ADJ knob. Turn clockwise to increase and counterclockwise to decrease.
6. Isolation resistance is given for input - output, input - ground and output - ground. It is tested at 500VDC.

For conformal coating option, add the suffix "-CC" to the model number (e.g. MPE-150C-12-CC).


Temperature Derating: 12V




Temperature Derating: 15, 24, 36, 48V




Input Voltage Derating




Efficiency vs Input Voltage: 12V (Full Load)




Efficiency vs Output Load: 12V




Efficiency vs Input Voltage: 24V (Full Load)




Efficiency vs Output Load: 24V



Efficiency vs Input Voltage: 48V (Full Load)





Efficiency vs Output Load: 48V



EMI Characteristics



Parameter	Standard	Criteria	Level
Radiated Emissions (RE)	CISPR32/EN55032		B
Conducted Emissions (CE)	CISPR32/EN55032		B
Harmonic Current	IEC/EN61000-3-2		A (≤80% load)
ESD	IEC/EN61000-4-2	A	Contact ±6kV/Air ±8kV
RS	IEC/EN61000-4-3	A	10V/m
EFT	IEC/EN61000-4-4	A	±4KV
Surge	IEC/EN61000-4-5	A	line to line ±2KV/line to ground ±4KV
CS	IEC/EN61000-4-6	A	10 Vr.m.s
Voltage Dips, Short, Interruption	IEC/EN61000-4-11	B	100% dip 1 period, 30% dip 25 periods, 100% interruption 250 periods

Mechanical Diagrams




THIRD ANGLE PROJECTION

Pin-Out	
Pin	Function
1	AC(L)
2	AC(N)
3	GRND
4	-Vo
5	-Vo
6	+Vo
7	+Vo



Position	Screw Spec	Length of Locking Screw L (max)	Torque (max)
2 - 4	M3	5mm	0.4N · m
7 - 8	M3	3mm	0.4N · m



Notes:

- All dimensions are typical in inches (mm)
- ADJ: Output voltage adjustable
- Wire range: Input: 22-10AWG (16-10AWG for pin 3)
Output: 12V, 15V: 14-10AWG
24V, 36V: 18-10AWG
48V: 20-10AWG
- Connector tightening torque: M3.5, Max 0.8N · m Max
- General tolerances: ±0.039 (±1.00)
- 1 - 9 any position must be connected to PE

Weight:

- 14.46 oz (410g)