

Specifications

FHD-200 Digital Signage Player

Media	
Video Playback Engine	H.264 4K x 2K@60p, H.265 4K x 2K@60p, MPEG-1/2/4, VC-1
Display Resolution	4K (3840 x 2160)@60fps
HDMI output	1 x HDMI
HDMI CEC	Yes
Purpose-Built Features	
Remote Settings & Configuration	Yes
Scheduled Power On/Off	Yes
Secured Data Connection (SSL/TLS)	Yes
IEEE 802.1X Authentication on WiFi	Yes
IEEE 802.1X Authentication on Ethernet	Yes
Proxy Server	Yes
Fail-Safe Protection / Auto Recovery	Yes
Administrative Password Protection	Yes
APK / Content URL Auto Launch Support	Yes

Media	
Presentation / Kiosk Mode Switcher	Yes
Remote Firmware / APK Update (OTA)	Yes
Real-time Clock (RTC)	Yes
Watchdog Timer	Yes, Independent watchdog
BLE Beacon	Yes
Supports Transmitter Mode	Yes
System	
CPU	ARM Quad-Core Cortex A53, 1.5GHz
GPU	Mali-450MP2
Auxiliary Audio Out	USB output
Memory	2GB DDR4
Storage	32GB
Independent Watchdog	Yes
Operating System	Android 12
I/O Interface	
Ethernet	1 x RJ45 (10/100 BASE-T)
WLAN	802.3 11 a/b/g/n/ac, Wi-Fi 5 (Optional)

Media	
USB	1 x USB 2.0 type A, 1 x USB 3.0 type A
ADB	1 x Micro USB for ADB
HDMI	1 x HDMI Out
Storage Expansion	1 x Micro SDXC slot, Max.:2TB
Power Input	1 x DC jack
Reset Button	Yes
LED Indicator	Yes
Power	
Power Adapter	DC 5V/2A
Mechanical	
Dimensions (WxDxH)	127 x 65 x 20 (mm)
Mounting	VESA mount kit, 75/75 (mm)
Housing	Metal
Antenna	External antenna (Optional)
Environment	
Operating Temperature	0°C to 60°C (32°F to 140°F)
Storage Temperature	-20°C to 70°C (-4°F to 158°F)