



SB-244-1J64

Industrial Fanless PC w/ Intel® Elkhart Lake Celeron® J6412 Processor



Features

- Intel® Celeron® J6412 CPU Elkhart Lake (2.0 GHz/2.6GHz)
- 1 x SDRAM DDR4 3200 MHz (max. 32G)
- Support 4 Gigabit LAN
- Support DP/HDMI video output
- Support SATA/M.2 SSD, M.2 WiFi, Mini-PCIe



HDMI

Over-voltage
Protection

USB 3.1



-10~60°C

Wide Voltage
RangeReversed
Power Insertion
Protection

System

CPU	Intel® Celeron® J6412 CPU Elkhart Lake (2.0 GHz/2.6GHz)
Memory	1 x SDRAM DDR4 3200 MHz SO-DIMM slot (max. 32G) 4GB DDR4 SO-DIMM pre-installed*(CTOS)
Graphics	Intel® UHD Graphics for 10 th Gen Intel® Processors
LAN chipset	1 x Intel I210AT GbE controller 3 x Intel I226-V 2.5GbE controllers
Watchdog Timer	Programmable 255 levels timer interval, from 1~255 sec/min

Storage

Device	1 x SATA 3.1 (2.5" HD) 1 x M.2 2242 (SATA3.0) 128GB M.2 SSD pre-installed*(CTOS)
--------	--

Audio

Type	1 x Audio(Line-out & Mic-in) Chip 888S/897
------	--

Power System

Power Input	12-24V DC, 2-pin phoenix connector
-------------	------------------------------------

OS

Windows 10, Ubuntu 20.04

Qualification

Certification	CE, FCC
---------------	---------

External I/O

Serial Ports	2 x RS232/RS422/RS485 (default RS-232) with auto flow control 2 x RS485 2 x RS232 (optional by internal pin head)
USB Ports	2 x USB3.1 4 x USB2.0 1 x USB2.0 (for security dongle)

LAN	4 x RJ45
Video Ports	1 x HDMI up to 4096 x 2160 @ 24 Hz 1 x DP up to 4096 x 2160 @ 60 Hz
GPIO Remote	1 x 8bit programmable GPIO (default 3.3V, 5V optional) (optional by internal pin head)
Remote	1 x SW
Indicators	1 x Power LED(Green for Power-on, Blink for Sleep mode, Off for Power-off)

Internal I/O

Expansion Slot	1 x Mini-PCIe slot(PCIe/USB2.0 signal supported) 1 x E-Key M.2 2230 slot(PCIe/USB2.0 signal supported) 1 x M.2 2242 SSD slot(SATA signal supported)
SIM Card	1 x SIM Card socket for 3G/4G module

Mechanical

Button	1 x Power button
Chassis	Aluminum Alloy
Dimension (W x H x D)	200 x 153 x 52.8 mm
Weight (Net)	1.5kg

Environmental


Operating Temp.	-10 ~ 60°C
Storage Temp.	-40 ~ 85°C
Operating Humidity	5 ~ 95% (non-condensing)
Random Vibration	5~500Hz, 2Grms, operation
Shock	Operation: 10G@11ms Non-operation: 30G@11ms
ESD	Contact 6KV, Air 10KV

*CTOS means Configure-to-Order Service.

All specifications are subject to change without notice.

SB-244-1J64

Dimensions



Ordering Information

SB-244-1J64	Barebone Fanless System Intel Celeron Elkhart Lake J6412, 4xLAN, 4xCOM(up to 6), 6xUSB, 1xHDMI, 1xDP, DC 12-24V power input
SB-244-1J64-R4S128	Fanless System with 4GB RAM & 128GB SSD, Intel Celeron Elkhart Lake J6412, 4xLAN, 4xCOM(up to 6), 6xUSB, 1xHDMI, 1xDP, DC 12-24V power input



Optional Accessories

PAC-60W-FSP-SPA R1.0	AC/DC ADAPTER KIT (W/UKCA),12V,60W,2 WIRE w/ USA POWER CORD
PAC-60W-FSP-SPA R1.1	AC/DC ADAPTER KIT (W/UKCA),12V,60W,2 WIRE w/ EU POWER CORD
PAC-60W-FSP-SPA R1.2	AC/DC ADAPTER KIT (W/UKCA),12V,60W,2 WIRE w/ UK POWER CORD
PAC-60W-FSP-SPA R1.3	AC/DC ADAPTER KIT (W/UKCA),12V,60W,2 WIRE w/ IN POWER CORD