



Rugged, reliable, cost-effective connectivity for critical industrial applications

Digi IX10 is a full-featured industrial cellular router built for troublefree reliability over a long service life — easy to deploy and centrally managed via **Digi Remote Manager**[°] (Digi RM), which is included in your **Digi 360** solution. (See page 2.)

Its flexible power and connectivity options make it a versatile and costeffective choice for industrial, digital signage, ATMs, lottery terminals, kiosks and other unattended retail applications that need to provide secure transactions over public and private cellular networks.

Digi IX10 can operate on public and private LTE networks, with features to assist in network control and management, such as dual SIMs for cellular failover connectivity, VLAN support, load balancing between cellular and Ethernet WANs, dual APNs and configurable APN search.

Digi IX10 features one Ethernet port and one RJ-50 serial port supporting both RS-232 and RS-485. In the event of an interruption to your primary network connection, Digi RM also provides secure out-of-band management of edge devices via Digi IX10's serial port and command-line interface.

Gain critical insights into your deployed devices and manage your network with Digi RM — the command center for your deployment. Digi RM is a cloud-based solution that facilitates easy setup, mass configuration, maintenance and support, even for thousands of devices. Digi RM empowers you to evaluate, update and configure your Digi products, while providing easy visibility into the health of your network. It also offers low-touch and no-touch provisioning.

Digi IX10 offers the convenience of a global SKU for simplified global distribution and deployment, as well as cost-optimized SKUs for North America, including a CBRS-only SKU.

Related Digi industrial IoT software and solutions

Digi IX40









Digi IX20

Digi IX30


Digi TX54

Digi Remote Manager°

Key features, benefits and applications

DIGI

- Compact and economical connectivity solution with industrial feature set for public and private cellular networks
- Redundant connectivity with dual SIMs and Digi SureLink[®]
- Global and regional bands with single part number to simplify distribution, deployment and management
- Meets U.S. government FIPS 140-2 cybersecurity standard
- Built-in Digi TrustFence[®] for device security, device identity and data privacy
- Digi Containers to enable powerful, cost-efficient applications
- Includes the **Digi 360** solution with warranty, customer care and **Digi Remote Manager** cloud management, enabling easy setup, mass configuration and management
- Ethernet port and single RJ-50 serial port (RS-232/485)
- C1D2 rated with IP30 enclosure





© Digi International Inc. All rights reserved. www.digi.com Singel 3 | B-2550 Kontich | Belgium | Tel. +32 (0)3 458 30 33 | info@alcom.be | www.alcom.be Rivium 1e straat 52 | 2909 LE Capelle aan den Ijssel | The Netherlands | Tel. +31 (0)10 288 25 00 | info@alcom.nl | www.alcom.nl

DIGI IX10 WITH DIGI 360

Digi 360

Digi 360 offers comprehensive IoT packaged solutions, including purpose-built devices, software and services to help customers optimize their IoT investments and maximize ROI. These solutions are designed to simplify IoT complexity, and ease the challenges enterprises face in configuring, deploying and managing their IoT initiatives. Your Digi 360 subscription is included with the purchase of Digi IX10, complete with Digi Remote Manager, warranty and customer care. Learn more at digi.com/digi360.



Management

Digi Remote Manager[®], our network orchestration platform, provides complete visibility and control, with configuration, remote monitoring, automation, security and OTA software update capabilities.



Device

High-performanace, purpose-built Digi devices, with integrated software, designed to meet the requirements of a wide range of enterprise, industrial, medical and transportation use cases.

Customer Care

The support plan provides 24 x 7 x 365 tier 1 support with 4-hour SLA for device and network troubleshooting to ensure customers can resolve issues quickly.



Warranty

Device warranty covering the full length of the Digi 360 subscription, to help customers maximize their technology investment while limiting risk.

Value-Added Services

Digi Containers



Digi Remote Manager enables deployment of custom applications via containers

Digi Containers simplify and centralize the process of building, deploying and running custom applications on devices managed with **Digi Remote Manager** as the central portal. Containers with custom programs or Python applications can be loaded via Digi RM on any device running the **Digi Accelerated Linux** operating system (DAL OS).

As an add-on service to Digi Remote Manager, Digi Containers are a powerful capability implemented via Lightweight Linux Containers (LXC). LXC tools enable developers to package up a custom application, with its dependencies and configuration, into a lightweight, portable bundle that shares only the running kernel with the host device.

*Digi Containers is available as value-added services with Digi Remote Manager.

24/7

DIGI IX10 WITH DIGI 360

Digi 360 Management and Security

Digi Accelerated Linux (DAL OS)

DAL OS is Digi's standard operating system integrated into Digi **Enterprise** (EX), **Industrial** (IX) and **Transportation** (TX) routers, **console servers** and **USB-connected devices**. Developed for speed and simplicity, DAL OS enables advanced capabilities that support today's demanding applications. **Learn more at digi.com/DAL**.

Digi Remote Manager (Digi RM)

Digi Remote Manager is a proven technology platform that brings networks to the next level, empowering networks — and the people who manage them — to work smarter. Digi RM transforms a multitude of dispersed IoT devices into a dynamic, intelligent network. It's easy to deploy, monitor and diagnose thousands of mission-critical devices from a single point of command on a desktop, tablet or phone. All the while, software-defined security diligently safeguards your entire Digi ecosystem. Learn more at digi.com/digi-remote-manager.

Digi RM infrastructure and security

- Hosted in a commercial-grade cloud server environment that meets SOC 1°, SOC 2° and SOC 3° standards
- Superior availability, operating at 99.9% or greater uptime
- Open APIs are available to support application development
- Comprehensive security controls to protect your data
- Member of the Center for Internet Security[®] (CIS[®])
- Enables compliance with security frameworks like ISO27002, HIPAA, NIST and more
- Earned Skyhigh's CloudTrust[™] Program highest rating of Enterprise-Ready

Digi TrustFence

The Digi TrustFence device security framework simplifies the process of securing multiple connected devices.



Designed for mission-critical applications, **Digi TrustFence** enables users to easily integrate device security, device identity, and data privacy capabilities into product design.

Digi TrustFence security for IoT devices is designed to grow and adapt with new and evolving threats.

Learn more at digi.com/trustfence.



DAL OS and Digi RM capabilities

- DAL OS with Digi Remote Manager: Remote console access, configuration templates, HTTP proxy, device event logs, configurable maintenance window
- Serial: Modbus, serial-over-TCP/UDP
- Customization: Python 3, Python pip, PyCharm integration, shell scripting, containers, MQTT client
- Troubleshooting: iPerf and nuttcp bandwidth testing, Find Me tool
- GNSS: NMEA/TAIP location forwarding to servers, geo-fencing
- Activate, monitor and diagnose your mission-critical devices through a single portal
- Schedule key operations including firmware updates and file management — on a single device or on a group of devices, keeping your network functionality up-to-date and maintaining compliance standards
- Manage edge devices out-of-band via console terminal access
- Monitor equipment health and connectivity across deployments
- Create detailed reports and real-time alerts for specified conditions
- Integrate device data through open APIs to gain deeper insights and control with third-party applications
- Report and alert on performance statistics, including connection
 history, signal quality, latency, data usage and packet loss

Built-in Security. Delivered.

- Secure boot: Programs and code running on the device are validated to be from an approved source or manufacturer
- Protected hardware ports: Internal and external I/O ports are hardened and access-controlled to prevent unwanted intrusion
- Authentication: Data authentication and device identity management options, with updated user and password settings
- Secure connections: Latest encryption protocols for data in motion and over-the-air (OTA) transmissions to ensure integrity
- **Ongoing monitoring and support:** Ongoing threat measurement and monitoring services, with external security audits



DIGI IX10 WITH DIGI 360 Specifications



Manage and configure Digi IX10 with Digi Remote Manager

SPECIFICATIONS	DIGI IX10 WITH DIGI 360*	
CELLULAR		
CERTIFICATIONS**	Visit digi.com/resources/certifications for latest certifications	
LTE CAT 4 GLOBAL (G4)	LTE Cat 4 Global: B1, B2, B3, B4, B5, B7, B8, B12, B13, B18, B19, B20, B25, B26, B28, B38, B39, B40, B41; 3G: B1, B2, B4, B5, B6, B8, B19; 2G EDGE / GPRS: 850 / 900 / 1800 / 1900 MHz	
LTE CAT 4 REGIONAL — NORTH AMERICA (N4)	LTE Cat 4 Regional — North America: B2, B4, B5, B12, B13, B14, B66, B71; 3G: B2, B4, B5	
LTE-ADVANCED CAT 6 CBRS-ONLY — NORTH AMERICA (C6)	LTE-Advanced Cat 6 CBRS-only — North America: B42, B43, B48 (CBRS)	
SIM SLOTS	(2) Mini-SIM (2FF)	
SIM SECURITY	Behind SIM cover, secured with screw (#1 Phillips)	
SOFTWARE AND MANAGEMENT*		
REMOTE MANAGEMENT	Digi Remote Manager; SNMP v2/v3 (user installed/managed)	
LOCAL MANAGEMENT	WebUI (HTTP/HTTPS); CLI (SSH)	
MANAGEMENT/ TROUBLESHOOTING TOOLS	FTP client, SCP; protocol analyzer with PCAP for Wireshark; event logging with syslog and SMTP client; NTP/SNTP; Nagios, Intelliflow, iPerf, Dynamic DNS, ping, traceroute	
MEMORY	256 MB RAM, 256 MB flash	
ETHERNET		
PORTS	(1) RJ-45; 10/100 Mbps (auto-sensing)	
SERIAL		
PORTS	 (1) RJ-50 10-pin (10P10C); RS-232/485; software selectable - RS-232 DTE (RXD, TXD, RTS, CTS, DTR, DCD, DSR, RI) - RS-485 (TX/RX+; RX/TX-); half-duplex 	
PHYSICAL		
DIMENSIONS (L x W x H)	118 mm x 88 mm x 35 mm (4.65 in x 3.46 in x 1.38 in)	
WEIGHT	0.39 kg (0.86 lb)	
STATUS LEDs	Power, Internet, SIM 1, SIM 2, SIM fail, LTE, signal strength (5)	
ENCLOSURE	Glass-filled polyphenylene sulphide (PPS) / IP30	
POWER REQUIREMENTS		
POWER INPUT	9 - 30 VDC, reverse polarity protection, 1.0 A maximum	
POWER CONSUMPTION	Configurable low-power modes; 1.5 W (light traffic flow), 2.5 W (peak data transmission); 1.25 W (low power mode, idle traffic)	
ACCESSORIES		
AVAILALBLE ACCESSORIES	Accessories not included. Available accessories: industrial extended temperature or commercial power supply (required), and cellular antennas, DIN rail clip and EIA 422/485 to RJ-45 connector (recommended / optional)	
ENVIRONMENTAL		
OPERATING TEMPERATURE	-40 °C to 70 °C (-40 °F to 158 °F); device performance may be impacted above 50 °C (122 °F)	
STORAGE TEMPERATURE	-40 °C to 85 °C (-40 °F to 185 °F)	
RELATIVE HUMIDITY	5% to 95% (non-condensing)	

*Includes the Digi 360 solution for Digi IX10 (1-year) with Digi Remote Manager, warranty and customer care. **Visit digi.com/resources/certifications for latest approvals and updates.

DIGI IX10 WITH DIGI 360 Specifications and Technologies



Manage and configure Digi IX10 with Digi Remote Manager

SPECIFICATIONS	DIGI IX10 WITH DIGI 360*
APPROVALS**	
CELLULAR	Visit digi.com/resources/certifications for latest cellular certifications and updates
SAFETY	IEC 62368-1, CB, EN 62311, UL 121201 9th Editio, CAN/CSA C22.2 NO.213-17
ENVIRONMENTAL	ROHS3
EMISSIONS / IMMUNITY	CE; RED; FCC Part 15, Subpart B; ICES-003; AU/NZS CISPR32
WARRANTY***	
PRODUCT WARRANTY	1-year

*Includes the Digi 360 solution for Digi IX10 (1-year) with Digi Remote Manager, warranty and customer care.

**Visit digi.com/resources/certifications for latest approvals and updates.

***Product warranty can be extended with **Digi 360** extensions or renewals.

ENTERPRISE SOFTWARE	DESCRIPTION	
PROTOCOL SUPPORT	HTTPS, FTP client, TLS v1.2, SCP (client and server), SFTP, SMTP client for use by scripts and the command line, SNMP (v2/v3), SSH; remote management via Digi Remote Manager ; protocol analyzer, ability to capture PCAP for use with Wireshark; DynDNS; dynamic DNS client compatible with BIND9/No-IP/DynDNS; captive portal, Intelliflow; Nagios, DNS server, NTP server, multicast, mDNS, IPerf	
SECURITY	IP filtering, stateful firewall, custom firewall rules (iptables), address and port translation; TLS 1.2 and above, OpenVPN client and serv VPN tunnels; Authentication: RADIUS, TACACS+; certificates; MAC address filtering; VLAN support	
VPN	IPSec with IKEv1, IKEv2, NAT Traversal; OpenVPN client and server; GRE VPN tunnels; Cryptology: SHA-1/256/384/512, MD5, RSA; Encryption: 3DES and AES up to 256-bit (CBC mode for IPsec); Diffie Hellman: DH groups 1-32 (CURVE448)	
ROUTING / FAILOVER	IP pass-through; NAT, NAPT with IP port forwarding; GRE; multicast routing; Routing protocols: RIP (v1, v2) OSPF, BGP; IP failover: VRR automatic failover, Digi SureLink	
OTHER PROTOCOLS	DHCP; dynamic DNS client compatible with No-IP/DynDNS	

*For a comprehensive list of operating system features, please visit digi.com/solutions/by-technology/dal-operating-system/features.

Featured Technologies



Product photos

Digi IX10 — front



Digi IX10 – back





DIGI IX10 WITH DIGI 360 Part Numbers

PART NUMBERS	DIGI IX10 WITH DIGI 360*	\sim
DIGI IX10 MODELS		
IX10-00G4	Digi IX10 — LTE Cat 4 Global, Ethernet, RS-232/485	
IX10-00N4	Digi IX10 — LTE Cat 4 Regional (North America), Ethernet, RS-232/485	
IX10-00C6	Digi IX10 — LTE-Advanced Cat 6 CBRS-only (North America), Ethernet, RS-232/485	

*Includes the Digi 360 solution for Digi IX10 (1-year) with Digi Remote Manager, warranty and customer care.

PART NUMBERS	AVAILABLE ACCESSORIES**
REQUIRED ACCESSORIES (INDUSTRIAL OR COMMERCIAL POWER SUPPLY)	
76002104	Industrial extended temperature power supply with plug tips for US, UK, EU, AU; -20 °C to 70 °C (-4 °F to 158 °F)
76002117	Commercial temperature power supply with plug tips for US, UK, EU, AU; 0 °C to 40 °C (32 °F to 104 °F)
RECOMMENDED AND OPTIONAL ACCESSORIES	
76002103	(1) Cellular antenna, order quantity 2
76002095	DIN rail clip kit
76000723	Connect EIA 422/485 devices to Digi products that have 10-pin RJ-45 connectors**

**Sold separately, unless otherwise noted.

PART NUMBERS	DIGI 360 EXTENSIONS AND RENEWALS
DIGI360-IX10-EXT-2YR	Digi 360 extension for two additional years for Digi IX10
DIGI360-IX10-EXT-4YR	Digi 360 extension for four additional years for Digi IX10
DIGI360-IX10-REN-1YR	Digi 360 renewal for one additional year for Digi IX10
DIGI360-IX10-REN-3YR	Digi 360 renewal for three additional years for Digi IX10
DIGI360-IX10-REN-5YR	Digi 360 renewal for five additional years for Digi IX10

VALUE-ADDED SERVICES
Digi Containers subscription — 1-year subscription

For more information, please visit **digi.com**.

DIGI.

© 2024 Digi International Inc. All rights reserved. All other trademarks are the property of their respective owners.



Singel 3 | B-2550 Kontich | Belgium | Tel. + 32 (0)3 458 30 33 | info@alcom.be | www.alcom.be Riviu 2909 LE Capelle aan den Ijssel | The Netherlands | Tel. +31 (0)10 288 25 00 | info@alcom.nl | www.alcom.nl