

AC/DC Power Encapsulated 3-40 W by Pairui

Represented by 



ASM Series

Universal input range(90~265Vac), board in-line type installation, EMC Class B without external components, design based on UL60950 and EN60950 standards, 3 year warranty.

Certifications

Input Range

Output

Output Power



90-265Vac

5 , 12 , 15 , 24 , 48

15W / 20W / 30W



ALR Series

Universal input range(85~265Vac), board in-line type installation, short circuit and over current protection, designed based on UL60950 and EN60950 standards, 3 year warranty.

Certifications

Input Range

Output

Output Power



85~265Vac

5 , 9 , 12 , 24 , ± 5 , ± 9 , ± 12 , ± 24 Vdc
 5W / 10W / 20W / 25W / 30W / 40W / 50W / 75W / 100W / 150W



ASD/ATR Series

Compact size, universal input voltage range, high voltage isolation 3000-4000Vac, 100% burn-in test, designed to UL60950-1 and EN60950-1 standards, 3 year warranty.

Certifications



Input Range

90~305Vac

Output

3.3 , 5 , 9 , 12 , 15 , 1W / 3W / 4W / 5W / 10W
24Vdc

Output Power



ASH Series

Universal input range(85~265Vac), board in-line type installation, short circuit and over current protection, single output, dual output and two outputs selection, designed based on UL60950 and EN60950 standards, 3 year warranty.

Certifications



Input Range

85-265Vac

Output

3.3 , 5 , 9 , 12 , 15 , 24 , 5W / 10W / 15W / 20W / 25W
±5 , ±12 , ±15 , ±24 ,
5/5 , 5/12 , 5/15 , 5/24

Output Power





AQR Series

Compact size, universal input range(85~265Vac), board in-line type installation, short circuit and over current protection, designed based on UL60950 and EN60950 standards, 3 year warranty.

Certifications



Input Range

85~265Vac

Output

5 , 9 , 12 , 24 , ± 5 , ± 9 , 1W / 3W / 5W / 10W / 15W
 ± 12 , ± 24 Vdc

Output Power

