

LX SERIES

APPLICATION Indoor Lighting, Spot Light, Cabinet Light, Down Light, Panel Light, Recessed Light



ELECTRICAL

Input: 90~264VAC/180~264VAC

Output: 240, 350, 700, 1050mA(CC Mode)

Power: 10W, 12W, 15W, 20W, 25W, 30W, 35W, 40W, 45W, 50W

FEATURES

- 3 Year Warranty
- Active Power Factor Correction
- Rating IP20
- Ambient Temperature: -25°C to +70°C
- Short Circuit, Over Voltage and Over Current Protections

LZ SERIES

APPLICATION Indoor Lighting, Spot Light, Cabinet Light, Down Light, Panel Light



ELECTRICAL

Input: 90~264VAC/180~264VAC

Output: 240, 350, 500, 700, 1050mA (CC Mode)

Power: 8W, 12W, 18W, 25W, 40W

FEATURES

- 3 Year Warranty
- Active Power Factor Correction
- Rating IP20
- Ambient Temperature: -25°C to +50°C
- Short Circuit, Over Voltage and Over Current Protections

LL SERIES

APPLICATION Indoor Lighting, Strip Light, Cabinet Light, Panel Light, Tri-Proof Light



ELECTRICAL

Input: 90~305VAC

Output: 300, 350, 400, 450, 500, 550, 600, 700, 750, 800, 900, 950, 1000, 1200, 1300, 1400, 1500, 1550mA (CC Mode)

Power: 20W, 40W, 60W

FEATURES

- 3 Year Warranty
- Active Power Factor Correction
- Rating IP20
- Ambient Temperature: -30°C to +50°C
- 3 in 1 Dimming Optional (0-10V, PWM, Resistor)
- No Flickering

LC SERIES

APPLICATION Indoor & Outdoor Lighting, Garden Light, Cabinet Light, Down Light



ELECTRICAL

Input: 90~305VAC

Output: 350, 450, 700, 1050, 1280, 1400, 1660mA (CC Mode)

Power: 20W, 30W, 40W

FEATURES

- 5 Year Warranty
- Active Power Factor Correction
- Rating IP67
- Ambient Temperature: -35°C to +70°C
- 0-10V Dimming

LF SERIES

APPLICATION Indoor & Outdoor Lighting, Garden Light, Cabinet Light, Down Light



ELECTRICAL

Input: 90~264VAC/180~264VAC

Output: 350, 500, 700, 1050, 1400, 1750, 2100, 2800, 3150mA (CC Mode)
5, 12, 15, 24, 36, 48Vdc (CV Mode)

Power: 35W, 60W, 100W, 150W

FEATURES

- 3~5 Year Warranty
- Active Power Factor Correction
- Rating IP67
- Ambient Temperature: -25°C to +70°C
- Short Circuit, Over Current and Over Voltage Protections

LG/LGS SERIES

APPLICATION Outdoor Lighting, Street Light, Tunnel Light, High/Low Bay Light, Flood Light



ELECTRICAL

Input: 90~305VAC

Output: 350, 450, 700, 1050, 1280, 1400, 1660, 1750, 2100, 2450, 2800, 3150, 3500, 4200, 4800mA (CC Mode)

Power: 30W, 40W, 50W, 60W, 75W, 85W, 100W, 120W, 150W, 185W, 200W, 250W

FEATURES

- 5 Year Warranty
- Active Power Factor Correction
- Rating IP67
- Ambient Temperature: -35°C to +70°C
- Short Circuit, Over Voltage, Over Current and Over Temperature Protections
- Optional Dimming(0-10V, PWM)

LGE SERIES

APPLICATION Outdoor Lighting, Street Light, Tunnel Light, High/Low Bay Light, Flood Light



ELECTRICAL

Input: 90~305VAC

Output: 700, 1050, 1400, 2100, 2450, 2800, 3150, 3500, 4200, 5000, 5500, 6300mA (CC & CV Mode)

Power: 60W, 75W, 80W, 100W, 120W, 150W, 200W, 250W

FEATURES

- 5 Year Warranty
- Active Power Factor Correction
- Rating IP65
- Ambient Temperature: -35°C to +70°C
- Short Circuit, Over Voltage, Over Current and Over Temperature Protections
- 3 in 1 Dimming (0-10V, PWM, Resistor)
- Adjustable Output Current (60%~100%)

