

# Focused Product List

Size	P/N	Glass Type	Resolution	OD(mm)	AA(mm)	Interface	Touch	Brightness (nits)	Op Temp	4W RTP	5W RTP	CTP	Controller
3.5	OT035ZQWDDN-00	TN	320*240	76.9*63.9*3.26	70.08*52.56	TTL	No	350	-20/+60	●			
4.0	OT040ZGDDDN-00	IPS	480*800	55.64*94.1*2.2	51.84*86.4	TTL	No	400	-20/+70			●	Focal
4.3	OT043ZWUDDN-01	TN	480*272	105.5*67.2*3.0	95.04*53.856	TTL	No	600	-20/+70	●			
5.7	OT057ZQUDDT-05	TN	320*240	144*104.6*14.8	115.2*86.4	TTL	4W RTP	320	-20/+70	●		●	Sitronix
5.7	OT057ZVUDDN-01	TN	640*480	127*98.43*7	115.2*86.4	TTL	No	900	-20/+70	●			
6.3	OT063AODDLV-00	TN	800*256	165*66.96*9.2	152.4*48.768	LVDS	No	500	-10/+70	●			
7.0	OT070GGDDDV-00	TN	800*480	165*106.4*6.3	152.4*91.44	TTL 18 bit	No	500	-20/+70	●		●	Ilitek/Sitronix
7.0	OT070GGDDL-00	TN	800*480	165*106.4*6.3	152.4*91.44	LVDS 18 bit	No	500	-20/+70	●		●	Ilitek/Sitronix
7.0	OT070CGWDLT-01	Ofilm	800*480	165*106.4*8.92	152.4*91.44	LVDS	4W RTP	400	-20/+70	●		●	Ilitek/Sitronix
7.0	OT070KGDDL-01	TN	800*480	165*106*4*8	152.4*91.44	LVDS	No	1000	-20/+70	●		●	Ilitek/Sitronix
7.0	OT070ZAWDLN-02	IPS	1024*600	165.75*105.39*3.4	154.2144*85.92	LVDS 24 bit	No	350	-20/+70			●	Sitronix
7.0	OT070MADDLV-10	TN	1024*600	165.75*105.39*5.0	153*90	LVDS 24 bit	No	1000	-20/+60			●	EETI
7.0	OT070VBWDLV-00	IPS	1280*800	161*107*6.15	149.76*93.6	LVDS	No	400	-20/+70			●	EETI
8.0	OT080FSDDL-00	TN	800*600	183*141*10.3	162*121.5	LVDS	No	400	-20/+70	●			
8.0	OT080FSDDDV-H0	TN	800*600	183*141*10.3	162*121.5	TTL	No	1000	-20/+70	●			
8.4	OT084DSUDLV-00	TN	800*600	203*145.9*5.7	170.4*127.8	LVDS 18 bit	No	700	-20/+70				
8.4	OT084ISUDLV-03	TN	800*600	199.5*149.0*9.75	170.4*127.8	LVDS 24 bit	No	600	-20/+70				
8.4	OT084ISUDLV-02	TN	800*600	199.5*149*9.75	170.4*127.8	LVDS 24 bit	No	1000	-20/+70				
8.4	OT084HSUDLVH0	TN	800*600	203*145.9*5.7	170.4*127.8	LVDS 24 bit	No	800	-20/+70				
9.0	OT090EGDDL-00	TN	800*480	210.7*127.065*15	198*111.696	LVDS	4W RTP	400	-20/+70	●			
10.1	OT101CBWDLV-02	IPS	1280*800	229.46*149.1*4.8	216.96*135.6	LVDS	No	500	-20/+70			●	EETI/Ilitek
10.1	OT101CBWDLV-01	IPS	1280*800	229.46*149.1*4.8	216.96*135.6	LVDS	No	1000	-20/+70			●	EETI/Ilitek
10.1	OT101CBWDLT-05	IPS	1280*800	252*172.6*10.43	216.96*135.6	LVDS	USB PCAP	480	-20/+70			●	EETI/Ilitek
10.1	OT101CBWDLT-06	IPS	1280*800	252*172.6*10.43	216.96*135.6	LVDS	USB PCAP	800	-20/+70			●	EETI/Ilitek
10.4	OT104KXWDLV00	IPS	1024*768	236.0*174.3*10.6	211.2*158.4	LVDS	No	600	-20/+70°C				
10.4	OT104KXWDLVH0	IPS	1024*768	236.0*174.3*10.6	211.2*158.4	LVDS	No	1000	-20/+70°C				
12.1	OT121ZXWDLV-00	IPS	1024*768	260.5*204*8.6	245.76*184.32	LVDS	No	600	-30/+85°C			●	EETI
12.1	OT121DXWDLT-00	IPS	1024*768	289.47*222.0*19.6	245.76*184.32	LVDS	USB PCAP	450	-20/+70°C			●	EETI
12.1	OT121ZBWDLV-00	MVA	1280*800	278*184*10	261.12*163.2	LVDS	No	400	-10/+70°C			●	EETI
12.1	OT121ABWDLV-H0	MVA	1280*800	278*184*10	261.12*163.2	LVDS	No	1000	-10/+70°C			●	EETI
15.0	OT150CXDDL-00	TN	1024*768	326.5*253.5*15.66	304.128*228.096	LVDS	No	1500	-20/+70°C			●	EETI
15.0	OT150ZXWDLV-00	IPS	1024*768	326.5*253.5*9.1	304.1*228.1	LVDS	No	500	-30/+80			●	EETI
21.5	OT215BFWDLV-H0	IPS	1920*1080	495.6*292.2*19.56	476.64*268.11	LVDS	No	400	0/+50°C			●	EETI
21.5	OT215BFWDLVH1	IPS	1920*1080	495.6*292.2*19.56	476.64*268.11	LVDS	No	800	0/+50°C			●	EETI