


# COM HPC CLIENT MODULE

## conga-HPC/cTLU



- COM HPC Client Size A
- Intel® Tiger Lake-UP3 high performing and low power Intel® Core™ processor
- Embedded/Industrial use condition
- Extended temperature options available
- PCI Express Gen 4
- Integrated high performance Xe (Gen 12) graphics with 96 EU
- AI/DL Instruction Sets including VNNI

## COM+HPC™

<b>Formfactor</b>	COM HPC, Size A (95 x 120 mm), Client Connector Pinout				
<b>CPU</b>	<b>General Embedded Versions</b> Intel® Core™ i7-1185G7E Processor      4 Cores / 8 Threads      12 MB cache      Int. Graphics with 96 EU      12-28W TDP Intel® Core™ i5-1145G7E Processor      4 Cores / 8 Threads      8 MB cache      Int. Graphics with 80 EU      12-28W TDP Intel® Core™ i3-1115G4E Processor      2 Cores / 4 Threads      6 MB cache      Int. Graphics with 48 EU      12-28W TDP  <b>Industrial Versions</b> Intel® Core™ i7-1185GRE Processor      4 Cores / 8 Threads      12 MB cache      Int. Graphics with 96 EU      12-28W TDP Intel® Core™ i5-1145GRE Processor      4 Cores / 8 Threads      8 MB cache      Int. Graphics with 80 EU      12-28W TDP Intel® Core™ i3-1115GRE Processor      2 Cores / 4 Threads      6 MB cache      Int. Graphics with 48 EU      12-28W TDP				
<b>DRAM</b>	Up to 2 SO-DIMM sockets for DDR4 memory modules up to 32 GByte each (64 GByte total) with 3200 MT/s				
<b>Graphics</b>	Integrated Xe (Gen 12) graphics engine with up to 96 EU (Execution Units)   Supporting 4 independent display units (4x 4k/2x 8K)   Enhanced media (AV1/12b) with up to 2 Vdbox   Next Gen IPU6 with DPHY2.1   HDMI 2.0/2.1   DP 1.4				
<b>Display</b>	3x DP/HDMI/DP++   1x eDP				
<b>Ethernet</b>	2x 2,5 GbE TSN Ethernet via Intel® i225				
<b>I/O Interfaces</b>	4x PCIe Gen4   8x PCIe Gen3 2x USB 4.0   2x USB 3.2   8x USB 2.0 2x SATA III (6Gb/s)   SPI   2x UART   12x GPIO   2x MIPI-CSI				
<b>Audio</b>	1x I2S   2x SoundWire				
<b>congatec Board Controller</b>	Multi Stage Watchdog   non-volatile User Data Storage   Manufacturing and Board Information   Board Statistics I <sup>2</sup> C bus (fast mode, 400 kHz, multi-master)   Power Loss Control   Hardware Health Monitoring   POST Code redirection				
<b>Embedded BIOS Features</b>	OEM Customization   Flash Update   based on AMI Aptio UEFI				
<b>Security</b>	Trusted Platform Module (TPM 2.0)				
<b>Power Management</b>	ACPI 5.0 with battery support				
<b>Operating Systems</b>	tbd				
<b>Power Consumption</b>	See user's guide for full details				
<b>Temperature</b>	Industrial:      Operating: -40 to +85°C      Storage: -40 to +85°C Commercial:      Operating: 0 to +60°C      Storage: -40 to +85°C				
<b>Humidity</b>	Operating: 10 - 90% r. H. non cond.      Storage: 5 - 95% r. H. non cond.				
<b>Size</b>	95 x 120 mm				

# conga-HPC/cTLU | Order Information

Article	PN	Description
conga-HPC/cTLU-i7-1185G7E	050600	COM HPC Size A module based on Intel® Core™ i7-1185G7E 4-core processor with 1.8GHz up to 4.4GHz turbo boost, 12MB cache, Intel® Iris® Xe Graphics with 96EU and dual channel DDR4 3200 MT/s memory interface (Intel Tiger Lake). Commercial temperature range.
conga-HPC/cTLU-i5-1145G7E	050601	COM HPC Size A module based on Intel® Core™ i5-1145G7E 4-core processor with 1.5GHz up to 4.1GHz turbo boost, 8MB cache, Intel® Iris® Xe Graphics with 80EU and dual channel DDR4 3200 MT/s memory interface (Intel Tiger Lake). Commercial temperature range.
conga-HPC/cTLU-i3-1115G4E	050602	COM HPC Size A module based on Intel® Core™ i3-1115G4E 2-core processor with 2.2GHz up to 3.9GHz turbo boost, 6MB cache, Intel® Iris® Xe Graphics with 48EU and dual channel DDR4 3200 MT/s memory interface (Intel Tiger Lake). Commercial temperature range.
conga-HPC/cTLU-i7-1185GRE	050610	COM HPC Size A module based on Intel® Core™ i7-1185GRE 4-core processor with 1.8GHz up to 4.4GHz turbo boost, 12MB cache, Intel® Iris® Xe Graphics with 96EU and dual channel DDR4 3200 MT/s memory interface (Intel Tiger Lake). Industrial temperature range.
conga-HPC/cTLU-i5-1145GRE	050611	COM HPC Size A module based on Intel® Core™ i5-1145GRE 4-core processor with 1.5GHz up to 4.1GHz turbo boost, 8MB cache, Intel® Iris® Xe Graphics with 80EU and dual channel DDR4 3200 MT/s memory interface (Intel Tiger Lake). Industrial temperature range.
conga-HPC/cTLU-i3-1115GRE	050612	COM HPC Size A module based on Intel® Core™ i3-1115GRE 2-core processor with 2.2GHz up to 3.9GHz turbo boost, 6MB cache, Intel® Iris® Xe Graphics with 48EU and dual channel DDR4 3200 MT/s memory interface (Intel Tiger Lake). Industrial temperature range.
conga-HPC/cTLU-CSA-VC-B	050650	Standard active cooling solution for high performance COM HPC module conga-HPC/cTLU with integrated vapor chamber, 45mm overall heat sink height and integrated 12V fan. All standoffs are with 2.7mm bore hole.
conga-HPC/cTLU-CSA-VC-T	050651	Standard active cooling solution for high performance COM HPC module conga-HPC/cTLU with integrated vapor chamber, 45mm overall heat sink height and integrated 12V fan. All standoffs are M2.5mm thread.
conga-HPC/cTLU-CSP-VC-B	050652	Standard passive cooling solution for high performance COM HPC module conga-HPC/cTLU with integrated vapor chamber, 44mm overall heat sink height. All standoffs are with 2.7mm bore hole.
conga-HPC/cTLU-CSP-VC-T	050653	Standard passive cooling solution for high performance COM HPC module conga-HPC/cTLU with integrated vapor chamber, 44mm overall heat sink height. All standoffs are with M2.5mm thread.
conga-HPC/cTLU-HSP-VC-B	050654	Standard heatspreader for high performance COM HPC module conga-HPC/cTLU with integrated vapor chamber, 13mm overall heat sink height. All standoffs are with 2.7mm bore hole.
conga-HPC/cTLU-HSP-VC-T	050655	Standard heatspreader solution for high performance COM HPC module conga-HPC/cTLU with integrated vapor chamber, 13mm overall heat sink height. All standoffs are with M2.5mm thread.
conga-HPC/EVAL-Client	065600	Evaluation Carrier Board for COM-HPC Client type Modules.

© 2020 congatec AG. All rights reserved.

All data is for information purposes only. Although all the information contained within this document is carefully checked, no guarantee of correctness is implied or expressed. Product names, logos, brands, and other trademarks featured or referred are the property of their respective trademark holders. These trademark holders are not affiliated with congatec AG. Product not yet released for Mass Production. Preliminary Version 1.0 – 2020/09/15